

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE NO.	SAMPLE NO.	PEN./TORVANE	SPT.-BLOW COUNT	COLOR	MATERIAL TYPE	CONSIS- TENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
BORING NO. <u>E3-07</u> DATE: BEGIN <u>10-16-62</u> PAGE <u>111</u>										
JOB NO. <u>1140127279</u> COMPLETE <u>10-16-62</u> Thin Walled Tube										
PROJECT <u>Lost Lake Placement Area</u> ☒ 3" ☐ 6"										
LOCATION <u>X=3,243,386.0144, Y=725,703.6613</u>										
ELEVATION OF HOLE _____										
MANUFACTURER'S DESIGNATION OF DRILL RIG <u>CF-1000 Marsh Buggy</u>										
GROUNDWATER: DEPTH <u>2</u> ft., ELEV. _____ ft., at end of Drilling										
WEATHER <u>SYNNY</u>										
DRILLER <u>Dempsey Gacaren</u> LOGGER <u>John A. Gentry</u>										
0		J 1				GRAY + LT BROWN	SAND	V. LOOSE	SILT	-w/ROOTS & CLAY SML
		X 2	1/2			GRAY	SAND	V. LOOSE	SILT	
5		X 3	1/2	2		GRAY	SAND	LOOSE	SILT	
		X 4	1/2	3		GRAY	SAND	LOOSE	SILT	-w/CLAY SML
		J 5	0.25			GRAY	CLAY	SOFT		SAMPLE FELL OUT OF TUBE
10		J 6	5/6	7		GRAY	SAND	M. DENSE		
		X 7	4/6	7		GRAY	SAND	M. DENSE		
15		X 8	6/9	9		GRAY	SAND	M. DENSE		
		J 9				GRAY	SILT	M. DENSE	SAND	
20			10	0.00		DARK GRAY	CLAY	V. SOFT		* DARK GRAY CLAY ~ 18'
			11	0.00		DARK GRAY	CLAY	V. SOFT		-w/ HYPOCARB ON 6 DAR 18-24
			12	0.25		DARK GRAY & CLAY	CLAY	SOFT		
25										
30										
35										