

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE NO.	PEN./TORVANE	SPT-BLOW COUNT	COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
BORING NO. <u>E3-05</u> DATE: BEGIN <u>10-16-02</u> PAGE <u>1/1</u>					JOB NO. <u>1140127279</u> COMPLETE <u>10-16-02</u> Thin Walled Tube				
PROJECT <u>Lost Lake Placement Ana</u>					☒ 3" ☐ 6"				
LOCATION <u>X=3,243,484.2331, Y=725,722.4520</u>					ELEVATION OF HOLE <u>22.88</u>				
MANUFACTURER'S DESIGNATION OF DRILL RIG <u>CR-1000 Marsh Buggy</u>					GROUNDWATER: DEPTH <u>3</u> ft., ELEV. <u> </u> ft., at end of Drilling				
WEATHER <u>SUNNY</u>					DRILLER <u>Dempsey Coaren</u> LOGGER <u>John A. Gentry</u>				
0		1	0.00		PEBBLES BELOW GRAY	CLAY	V. SOFT		-w/ R 0075 SAND SMS
		2			GRAY & LT BROWN	SAND	V. LOOSE	SILT	
-5		3	12		DARK GRAY	SAND	LOOSE		-w/ HYDROCARBON OIL 4.10
		4	56		GRAY	SAND	M. DENSE		
		5	55		GRAY	SAND	M. DENSE		
-10		6	0.25		GRAY & BROWN	CLAY	SOFT		-w/ SAND SMS
		7	123		DARK GRAY	SAND	LOOSE		
-15		8	356		GRAY	SAND	M. DENSE		
		9	5712		GRAY	SAND	M. DENSE	SILT	
		10	6913		GRAY	SAND	M. DENSE	SILT	
-20		11	0.00		DARK GRAY	CLAY	V. SOFT		* DARK GRAY CLAY @ 20' -w/ HYDROCARBON OIL @ 20'-26' -w/ SAND SMS @ 20'
		12	0.00		DARK GRAY	CLAY	V. SOFT		
-25		13	0.00		DARK GRAY	CLAY	V. SOFT		
-30									
-35									