

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE NO.	PEN./TORVANE	SPT.-BLOW COUNT	COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
BORING NO. <u>E3-01</u> DATE: BEGIN <u>10-15-02</u> PAGE <u>1/1</u> JOB NO. <u>1140127279</u> COMPLETE <u>10-15-02</u> Thin Walled Tube PROJECT <u>Lost Lake Placement Area</u> ☒ 3" ☐ 6" LOCATION <u>X=3,243,680.6705, Y=725,760.0333</u> ELEVATION OF HOLE <u>17.59</u> MANUFACTURER'S DESIGNATION OF DRILL RIG <u>CF-1000 Marsh Buggy</u> GROUNDWATER: DEPTH <u>2</u> ft., ELEV. _____ ft., at end of Drilling WEATHER <u>SUNNY & WINDY</u> DRILLER <u>Dempsey Coates</u> LOGGER <u>John A. Gentry</u>									
0		1	0.75		REDDISH BROWN + GRAY	CLAY	MEDIUM STIFF		-W/SPD SML
		2			GRAY + LT BROWN	SAND	V. LOOSE		-W/CLAY SML
5		3	0.00		GRAY + BROWN	CLAY	V. SOFT		
		4			GRAY	SAND	M. DENSE	SILT	
		5	5.68		GRAY	SAND	M. DENSE	SILT	*DARK GRAY CLAY @ 10'
10		6	0.00		DARK GRAY	CLAY	V. SOFT		SAMPLE BULGE
		7	0.00		DARK GRAY	CLAY	V. SOFT		-W/HYDROCARBON @ 10-16'
15		8	0.00		DARK GRAY + GRAY	CLAY	V. SOFT		
20									
25									
30									
35									

J = JAR SAMPLE