

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE NO.	PEN./TORVANE	SPT.-BLOW COUNT	BORING NO. <u>EIB-01</u> DATE: BEGIN <u>10-18-02</u> PAGE <u>111</u> JOB NO. <u>1140127279</u> COMPLETE <u>10-18-02</u> Thin Walled Tube ☒ 3" ☐ 6" PROJECT <u>Lost Lake Placement Area</u> LOCATION <u>Z=3,243,577.303, Y=726,792.175</u> ELEVATION OF HOLE _____ MANUFACTURER'S DESIGNATION OF DRILL RIG <u>CF-1000 Marsh Buggy</u> GROUNDWATER: DEPTH <u>16</u> ft., ELEV. _____ ft., at end of Drilling WEATHER <u>PARTLY CLOUDY</u> DRILLER <u>Dempsey Gearen</u> LOGGER <u>John A. Gentry</u>				
					COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
0		1	3.50		REDDISH BROWN + GRAY	CLAY	V. STIFF		
		2	3.25		REDDISH BROWN + GRAY	CLAY	V. STIFF		
5		3	1.50		REDDISH BROWN + GRAY	CLAY	STIFF		w/Calc Nods
		4	0.50		REDDISH BROWN + GRAY	CLAY	M. STIFF		
		5	0.50		REDDISH BROWN + GRAY	CLAY	M. STIFF		
10		6	0.75		REDDISH BROWN + GRAY	CLAY	M. STIFF		
		7	0.75		REDDISH BROWN + GRAY	CLAY	M. STIFF		w/ SAND SMS
15		8	0.75		REDDISH BROWN + GRAY	CLAY	M. STIFF		
		9			GRAY	SAND			
		10	1.00		BROWN + GRAY	CLAY	STIFF		
20		11	0.75		GRAY + BROWN	CLAY	M. STIFF		
		12	0.75		GRAY	CLAY	M. STIFF		
25		13	0.00		DARK GRAY + GRAY	CLAY	V. SOFT		* DARK GRAY CLAY w 24' w/ HYDRO CARBON O DARK 4-20' w/ SLT SMS ON TOP 24'
		14	0.00		DARK GRAY	CLAY	V. SOFT		
		15	0.00		DARK GRAY	CLAY	V. SOFT		w/ SAND ON BOTTOM 30'
30									
35									J = JAR SAMPLE