

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE NO.	PEN./TORVANE	SPT.-BLOW COUNT	COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
BORING NO. <u>B4-20</u> DATE: BEGIN <u>10-12-02</u> PAGE <u>1/1</u> JOB NO. <u>1140127279</u> COMPLETE <u>10-12-02</u> Thin Walled Tube PROJECT <u>Lost Lake placement Area</u> ☒ 3" ☐ 6" LOCATION <u>X=3,242,436.835, Y=724,932.997</u> ELEVATION OF HOLE _____ MANUFACTURER'S DESIGNATION OF DRILL RIG <u>Pontoon mounted - Marsh Buggy</u> GROUNDWATER: DEPTH <u>1</u> ft., ELEV. _____ ft., at end of Drilling WEATHER <u>SUNNY</u> DRILLER <u>Dempsey Green</u> LOGGER <u>John A. Gentry</u>									
0		1	0.00		BROWN & GRAY	CLAY	V. SOFT		w/ROOTS
		J 2			BROWN & GRAY	SAND	V. LOOSE	SILT	
		3	0.00		BROWN & GRAY	CLAY	V. SOFT		
5		J 4			GRAY & LT BROWN	SAND	V. LOOSE	SILT	
		X 5	2		GRAY	SAND	V. LOOSE	SILT	
10		6	0.00		DARK GRAY	CLAY	V. SOFT		DARK GRAY CLAY @ 8' w/ HYDROCARBON @ 8'-14'
		7	0.00		DARK GRAY	CLAY	V. SOFT		
		8	0.00		DARK GRAY	CLAY	V. SOFT		
15									
20									
25									
30									
35									

J = JAR SAMPLE