

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE NO.	SAMPLE NO.	PEN./TORVANE	SPT.-BLOW COUNT	BORING NO. <u>E4-03</u> DATE: BEGIN <u>10-15-02</u> PAGE <u>1 11</u> JOB NO. <u>1140127279</u> COMPLETE <u>10-15-02</u> Thin Walled Tube PROJECT <u>Lost Lake Placement Area</u> ☒ 3" ☐ 6" LOCATION <u>X=3,243,222.276, Y=724,573.733</u> ELEVATION OF HOLE _____ MANUFACTURER'S DESIGNATION OF DRILL RIG <u>Pontoon mounted - Marsh Buggy</u> GROUNDWATER: DEPTH <u>2</u> ft., ELEV. _____ ft., at end of Drilling WEATHER <u>SUNNY</u> DRILLER <u>Dempsey Green</u> LOGGER <u>John A. Gentry</u>				
						COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
0		J 1				GRAY + Lt BROWN	SAND	V. LOOSE	SILT	-w/ R0075 CLAY SMS & shell FRAG.
		J 2				GRAY + Lt BROWN	SAND	V. LOOSE	SILT	-w/ CLAY SMS
5		X 3	2			GRAY	SAND	LOOSE	SILT	
		X 4	2	3		GRAY	SAND	LOOSE	SILT	
		X 5	6	7, 10		GRAY	SAND	M. DENSE		
10		X 6	7	9, 12		GRAY	SAND	M. DENSE		
		X 7	6	10, 12		GRAY	SAND	M. DENSE		
15		X 8	7	10, 13		GRAY	SAND	M. DENSE		
		X 9	6	9, 11		GRAY	SAND	M. DENSE		* DARK GRAY CLAY @ 18'
20			10	1, 0		GRAY + DK GRAY	CLAY	STIFF		-w/ SAND SMS
			11	0.75		GRAY + DK GRAY	CLAY	M. STIFF		-w/ HYDRO-CARBON OIL @ 18-24'
		J 12	0.00			DARK GRAY	CLAY	V. SOFT		-w/ SAND SMS
25										SAMPLE FELL OUT OF TUBE
										J = JAR SAMPLE
30										
35										