

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE NO.	PEN./TORVANE	SPT.-BLOW COUNT	COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
BORING NO. <u>SI-06</u> DATE: BEGIN <u>10-10-02</u> PAGE <u>1/1</u> JOB NO. <u>1140127279</u> COMPLETE <u>10-10-02</u> Thin Walled Tube PROJECT <u>Lost Lake Placement Area</u> ☒ 3" ☐ 6" LOCATION <u>X=3,241,660.425, Y=724,080.982</u> ELEVATION OF HOLE _____ MANUFACTURER'S DESIGNATION OF DRILL RIG <u>CF-1000 Marsh Buggy</u> GROUNDWATER: DEPTH <u>4</u> ft., ELEV. _____ ft., at end of Drilling WEATHER <u>CLOUDY</u> DRILLER <u>Dempsey Green</u> LOGGER <u>John A. Gentry</u>									
0		1	6.00		REDDISH BROWN GRAY	CLAY	V. SOFT		-w/ROOTS SAND SMS
		2	0.00		REDDISH BROWN GRAY	CLAY	V. SOFT		-w/ SAND SMS
5		3	0.5		REDDISH BROWN	CLAY	M. STIFF		-w/ SAND SMS
		4			GRAY	SAND	V. LOOSE	SILT	
		5	0.00		REDDISH BROWN GRAY	CLAY	V. SOFT		-w/ SAND SMS
10		6			GRAY	SAND	V. LOOSE	SILT	SAND 9' 9" / 10
		7			GRAY	SAND	V. LOOSE	SILT	
		8	0.00		OK GRAY	CLAY	V. SOFT		* DARK GRAY CLAY @ 11'
		9	0.00		DARK GRAY	CLAY	V. SOFT		-w/ SAND SMS -w/ HYDRO CARBON (DARK) 11'-18'
15		10	0.00		DARK GRAY	CLAY	V. SOFT		SAMPLE FEW GUT OF TUBE
		11	0.00		DARK GRAY	CLAY	V. SOFT		SAMPLE BLALPC
20									
									JAR SAMPLE
25									
30									
35									