

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE	SAMPLE NO.	PEN./TORVANE SPT.-BLOW COUNT	BORING NO. <u>W3-21</u> DATE: BEGIN <u>9-26-02</u> PAGE <u>1 11</u> JOB NO. <u>1140127279</u> COMPLETE <u>9-26-02</u> Thin Walled Tube PROJECT <u>Lost Lake Placement Area</u> ☒ 3" ☐ 6" LOCATION <u>X=3238,333.57, Y=725,204.38</u> ELEVATION OF HOLE <u>16.87</u> MANUFACTURER'S DESIGNATION OF DRILL RIG <u>Pontoon mounted - Marsh Bore</u> GROUNDWATER: DEPTH _____ ft., ELEV. _____ ft., at end of Drilling WEATHER <u>PARTLY CLOUDY</u> DRILLER <u>Dempsey Garen</u> LOGGER <u>John A. Gentry</u>				
					COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
0			1	0.00	BROWN GRAY	CLAY	V. SOFT		BROWN CLAY 0-8' w/ roots
		J	2	0.00	DK GRAY	CLAY	V. SOFT		SAMPLE BULGET
		J	3		GRAY	SAND	V. LOOSE		
5		J	4	WOH 18"	BROWN GRAY	SAND	V. LOOSE	SILT	
		J	5	WOH 18"	BROWN GRAY	SAND	V. LOOSE	SILT	
			6	0.00	DK GRAY GRAY	CLAY	V. SOFT		
10			7	0.75	DK GRAY GRAY	CLAY	V. SOFT		GRAY CLAY ON BOTTOM 9' 10" - 10' PEN. 0.75 MEDIUM STIFF
		J	8		GRAY	SILT	V. LOOSE		- W/ WOOD ON BOTTOM 12' - W/ WOOD
15			9		GRAY	CLAY	V. SOFT		- W/ SAND & SILT SM(S) 15.5-16'
		J	10		GRAY	SILT	V. LOOSE		
20									
25									
30									
35									

J = JAR SAMPLE

WOH = WEIGHT OF HAMMER