

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE NO.	PEN./TORVANE SPT.-BLOW COUNT	BORING NO. <u>W3-19</u>	DATE: BEGIN <u>9-26-02</u>	PAGE <u>1 11</u>		
		SAMPLE NO.		JOB NO. <u>1140127279</u>	COMPLETE <u>9-26-02</u>	Thin Walled Tube		
				PROJECT <u>Lost Lake Placement Area</u>	☒ 3"	☐ 6"		
				LOCATION <u>X=3,238,234.50, Y=725190.79</u>				
				ELEVATION OF HOLE <u>16.48</u>				
				MANUFACTURER'S DESIGNATION OF DRILL RIG <u>Pontoon mounted - Marsh Buggy</u>				
				GROUNDWATER: DEPTH <u>1</u> ft., ELEV. _____ ft., at end of Drilling				
				WEATHER <u>CLOUDY</u>				
				DRILLER <u>Dempsey Goren</u>	LOGGER <u>John A. Gentry</u>			
				COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
0		1		BROWN	CLAY	V. SOFT		- WIROTS 0-7
		2	0.00	GRAY	CLAY	V. SOFT		
		3		GRAY + BROWN	SILT	V. LOOSE	SAND	
5		3	11	GRAY + BROWN	SILT	V. LOOSE		
		4		GRAY	SILT	V. LOOSE	CLAY	
		5	0.00	DK GRAY	CLAY	V. SOFT		
10		6	0.00	GRAY	CLAY	V. SOFT		
		7	0.00	DK GRAY	CLAY	V. SOFT		
		8		GRAY	SAND	V. LOOSE	SILT	
		9	0.00	DK GRAY	CLAY	V. SOFT		- SAMPLE Bulge on extruder
15		10		GRAY	SILT	V. LOOSE		
								J: Jar Sample
20								
25								
30								
35								