

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE	SAMPLE NO.	PEN./TORVANE SPT.-BLOW COUNT	BORING NO. <u>W3-06</u> DATE: BEGIN <u>9-24-02</u> PAGE <u>1/1</u> JOB NO. <u>1140127279</u> COMPLETE <u>9-24-02</u> Thin Walled Tube PROJECT <u>Lost Lake Placement Area</u> ☒ 3" ☐ 6" LOCATION <u>X=3,237,590.52, Y=725,102.49</u> ELEVATION OF HOLE <u>19.1</u> MANUFACTURER'S DESIGNATION OF DRILL RIG <u>Track Mounted-Marsh Buggy</u> GROUNDWATER: DEPTH <u>2</u> ft., ELEV. _____ ft., at end of Drilling WEATHER <u>PARTLY CLOUDY</u> DRILLER <u>Dempsey Gerean</u> LOGGER <u>John A. Gentry</u>				
					COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
0		J	1		GRAY + BROWN	SAND	V. LOOSE	SILT	
			2	0.00	DARK GRAY	CLAY	V. SOFT		
			3	0.00	DARK GRAY	CLAY	V. SOFT		
5			4	0.00	DARK GRAY + BROWN	CLAY	V. SOFT		
			5	0.00	DARK GRAY	CLAY	V. SOFT		-w/ HYDROCARBON OIL
10			6	0.00	DARK GRAY	CLAY	V. SOFT		-w/ HYDROCARBON OIL
			7	0.00	DARK GRAY	CLAY	V. SOFT		-w/ HYDROCARBON OIL
			8	0.00	DARK GRAY	CLAY	V. SOFT		-w/ HYDROCARBON OIL
15			9	0.00	DARK GRAY	CLAY	V. SOFT		-w/ HYDROCARBON OIL
20									
25									
30									
35									

J = JAR SAMPLE