

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE	SAMPLE NO.	PEN./TORVANE	SPT.-BLOW COUNT	BORING NO. <u>W3-04</u> DATE: BEGIN <u>9-24-02</u> PAGE <u>1/1</u> JOB NO. <u>1140127279</u> COMPLETE <u>9-24-02</u> Thin Walled Tube PROJECT <u>Lost Lake Placement Area</u> ☒ 3" ☐ 6" LOCATION <u>X=3,237,491.45</u> , <u>Y=725,088.91</u> ELEVATION OF HOLE <u>20.2</u> MANUFACTURER'S DESIGNATION OF DRILL RIG <u>Track Mounted-Marsh Buggy</u> GROUNDWATER: DEPTH <u>4</u> ft., ELEV. _____ ft., at end of Drilling WEATHER <u>PARTLY CLOUDY</u> DRILLER <u>Dempsey Gorman</u> LOGGER <u>John A. Gentry</u>				
						COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
0		J	1			GRAY BROWN	SAND	V. LOOSE	SILT	-w/ roots
			2	0.75		GRAY	CLAY	M.F. DZUM STIFF		-w/ sand sm (H)
5		J	3			GRAY	SAND	M. LOOSE	SILT	
		X	4	1.014		GRAY	SAND	V. LOOSE	SILT	
			5	0.00		GRAY + BROWN	CLAY	V. SOFT		
10			6	0.06		DARK GRAY	CLAY	V. SOFT		-w/ HYDRO CARBON OIL
			7	0.00		DARK GRAY	CLAY	V. SOFT		-w/ HYDRO CARBON OIL
15			8	0.00		DARK GRAY	CLAY	V. SOFT		-w/ HYDRO CARBON OIL
			9	0.00		DARK GRAY	CLAY	V. SOFT		-w/ HYDRO CARBON OIL
20										
25										
30										
35										

J = JAR SAMPLE