

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET	SAMPLE NO.	PEN./TORVANE	SPT.-BLOW COUNT	BORING NO. <u>W 3-03</u> DATE: BEGIN <u>9-24-02</u> PAGE <u>1/1</u>				
				JOB NO. <u>1140127279</u> COMPLETE <u>9-24-02</u> Thin Walled Tube				
				PROJECT <u>Lost Lake, Placement Area</u> ☒ 3" ☐ 6"				
				LOCATION <u>X=3,237,441.92, Y=725,082.11</u>				
				ELEVATION OF HOLE <u>22-4</u>				
				MANUFACTURER'S DESIGNATION OF DRILL RIG <u>Track Mounted-Marsh Buggy</u>				
				GROUNDWATER: DEPTH <u>6</u> ft., ELEV. <u></u> ft., at end of Drilling				
				WEATHER <u>PARTLY CLOUDY</u>				
				DRILLER <u>Dempsey Gerean</u> LOGGER <u>John A. Gentry</u>				
				COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
0	1	0.00		BROWN + PK GRAY	CLAY	V. SOFT		- w/ Sand SM(S)
	2	0.00		DARK GRAY	CLAY	V. SOFT		- w/ Sand SM(S)
5	3	0.00		DARK GRAY	CLAY	V. SOFT		- w/ HYDROCARBON ODOR
	4	0.00		DARK GRAY	CLAY	V. SOFT		- w/ HYDROCARBON ODOR
	5	0.00		DARK GRAY	CLAY	V. SOFT		- w/ HYDROCARBON ODOR
10	6	0.00		DARK GRAY	CLAY	V. SOFT		- w/ HYDROCARBON ODOR
	7	0.00		DARK GRAY	CLAY	V. SOFT		- w/ HYDROCARBON ODOR
15	8	0.00		DARK GRAY	CLAY	V. SOFT		- w/ HYDROCARBON ODOR
	9	0.00		DARK GRAY	CLAY	V. SOFT		- w/ HYDROCARBON ODOR
20	10	0.00		DARK GRAY	CLAY	V. SOFT		- w/ HYDROCARBON ODOR
25								
30								
35								