

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE NO.	PEN./TORVANE SPT.-BLOW COUNT	COLOR	MATERIAL TYPE	CONSIS- TENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
BORING NO. <u>W3-01</u> DATE: BEGIN <u>9-24-02</u> PAGE <u>1/1</u>								
JOB NO. <u>1140127279</u> COMPLETE <u>9-24-02</u> Thin Walled Tube								
PROJECT <u>Lost Lake Placement Area</u> ☒ 3" ☐ 6"								
LOCATION <u>X=723 7362.58</u> <u>Y=725 073.56</u>								
ELEVATION OF HOLE <u>Appx. 25.4</u>								
MANUFACTURER'S DESIGNATION OF DRILL RIG <u>Track Mounted-Marsh Buggy</u>								
GROUNDWATER: DEPTH <u>20</u> ft., ELEV. _____ ft., at end of Drilling								
WEATHER <u>PARTLY CLOUDY</u>								
DRILLER <u>Dempsey Gercan</u> LOGGER <u>John A. Gentry</u>								
0	1	1.75	BROWN + GRAY	CLAY	STIFF		- W/ SHELL & SHELL FRAG	
	2	0.75	BROWN + GRAY	CLAY	MEDIUM STIFF		- W/ SAND SMP & SHELL FRAG	
	3	1.0	BROWN + GRAY	CLAY	STIFF		- W/ Calc Nods & SHELL FRAG	
5	4	0.75	BROWN + GRAY	CLAY	MEDIUM STIFF		- W/ Calc Nods & SHELL FRAG	
	5	1.0	BROWN + GRAY	CLAY	STIFF		- W/ Sq SM (S) & Calc Nods & SHELL FRAG	
10	6	1.0	BROWN + GRAY	CLAY	STIFF		- W/ Sq SM (S) & Calc Nods & SHELL FRAG	
	7	0.75	GRAY + BROWN	CLAY	MEDIUM STIFF			
15	8	0.75	GRAY + BROWN	CLAY	MEDIUM STIFF		- W/ WOOD	
	9	1.0	GRAY	CLAY	STIFF		- W/ WOOD	
	10	0.5	GRAY	CLAY	MEDIUM STIFF		- W/ WOOD	
20	11	1.2	GRAY	SAND	V. LOOSE			
	12	1.1	GRAY + BROWN	SAND	V. LOOSE			
25							J = JAR SAMPLE	
30								
35								