SWG Form 267(C)
28 Jan 1965

PROJECT: P.A.C.C.W.W.

LOCATION: Channel to La Quinta

TEST DATA SUMMARY

BORING NO. 3st-25

DATE DRILLED 23 Feb 1965

FIELD NO.	DEPTH	CLASSIFICATION ELEVATION TOP BORING _____	SYMBOL	CONSISTENCY	POCKET (1) PENETROMETER	STAN. PENET. BLOWS/FT (2)	MOISTURE CONTENT %	DRY DENSITY p.c.f.	L.L.	P.L.	BAR L.S.	SIEVE ANALYSIS PERCENT GRVL	SAND	FINES	INIT. WT.	ACC. WT. RTND. SIEVE NO. (3) NO. 4	NO. 10	NO. 40	NO. 200
	0-26	Water																	
J-1	26-28	Brown sandy clay, w/calc	CL				30.8				7.0	6	38	56	50	2.8	5.0	6.5	22.0
C-1	28-30½	Nod from 26-33		VST	2.25														
C-2	30½-33			VST	2.25														
C-3	33-35½	Brown silty sand from	SM		2.00		18.3	108			1.0	3	57	40	50	1.3	1.5	1.9	30.0
J-2	35½-37	33-50.5			VD	31													
X	37-40½	Calc Nod																	
J-3	40½-42				VD	33	20.5				OP	2	77	21	50	1.0	2.0	3.0	39.5
X	42-45½																		
J-4	45½-47				VD	38	24.5				0.0	2	60	38	50	0.8	1.0	1.0	31.0
X	47-50½																		
J-5	50½-52	Brown sandy clay, w/calc Nod	CL		VD	83	20.4				6.0	18	30	52	50	6.5	8.8	10.0	24.0
		from 50.5-52'																	
		Sta 180+00																	
		Tide +1.4 @ 9:30 AM																	

KEY: CONSISTENCY — COHESIVE SOILS: VS S M ST VS H; CONSISTENCY — COHESIONLESS SOILS: VL L M D VD

(1) Tons/Sq.Ft. Unconfined Compressive Strength
(2) Split Barrel Sampler

BORING NO. 3st-25