

SWG Form 267(C)
28 Jan 1965

PROJECT: P.A.C.C.W.W.

LOCATION: Channel to LaQuinta

TEST DATA SUMMARY

BORING NO. 3st-22

DATE DRILLED 19 Feb 1965

FIELD NO.	DEPTH	CLASSIFICATION ELEVATION TOP BORING _____	SYMBOL	CONSISTENCY	POCKET (1) PENETROMETER	STAN. PENET. BLOWS/FT (2)	MOISTURE CONTENT %	DRY DENSITY P. c. f.	L.L.	P.L.	BAR L.S.	SIEVE ANALYSIS								
												PERCENT			INIT. WT.	ACC. WT. RTND. SIEVE NO. (3)				
												GRVL	SAND	FINES		NO. 4	NO. 10	NO. 40	NO. 200	
	0-37	Water																		
J-1	37-40 ^s	Gray sandy clay, w/calc	CL																	
J-2	40 ^s -42	Nod From 37-42'				69.0					10.0	2	36	62	50	1.0	2.0	3.8	19.0	
J-3	42-44	Brown silty sand, w/calc nod	SM			20.6					2.0	23	58	19	684	155	216	248	554	
J-4	44-45 ^s	From 42-47'		VD	20															
X	45 ^s -47																			
C-1	47-49 ^s	Brown sandy clayey silt 47-50.5'	CL	ST	1.0	72.4	102				4.0	0	20	80	50	00	03	0.4	10.0	
X	49 ^s -50 ^s																			
J-5	50 ^s -52	Brown sandy silt, w/calc nod From 50.5'-52'	ML			21.0					1.0	20	34	46	50	100	120	130	270	
																	</			

KEY: CONSISTENCY — COHESIVE SOILS
VS S M SZ VS H VL L M D VD
CONSISTENCY — NONCOHESIVE SOILS

(1) Tons/Sq.Ft. Unconfined Compressive Strength
(2) Split Barrel Sampler

BORING NO. 3st-22