Houston Ship Channel

LOG OF BORING NO. 35T-170

Tide + 1.5 @ 7.00 AM

TYPE: 3" Shelby Tube LOCATION: Sta. 940+00

DEPTH FT	SYMBOL	SAMPLES	DESCRIPTION OF MATERIAL (SURF. EL.)	BLOWS PER FT	UNIT DRY WT. LBS/CU.FT.	ELEVATION FT
			Water Depth 9.0'			
10	CL		Gray-Tan-Red, Clay		109	
			L.S. 12.0 0-11-89			
			V/Stiff		112	
15			Sandstone & Calcareous Nodules 14-16.5'		106	
			L.S. 17.0 0-11-89			
			L.S. 15.0 0-7-93		103	
20			Clay w/Cemented Sandstone 19-21.5'		112	
			L.S. 19.0 0-6-94		109	4.5
25			Calcareous Nodules			
			L.S. 20.0 0-19-86		108	
	SM		Red, Silty Sandy V/Dense	95		
30						
35			L.S. 10.0 0-56-44	45		
40				42		
			Red, Clay Hard		97	4.25
45	CL					4.25
			L.S. 14.0 0-1-99		105	4.25
50					102	4.0
					97	

POCKET PENETROMETER TONS / SQ. FT.: 0.5, 1.0, 1.5, 2.0, 2.5, 3.0

PLASTIC LIMIT — WATER CONTENT, % — LIQUID LIMIT: 10, 20, 30, 40, 50, 60

COMPLETION DEPTH 52.0'

DATE 28 May '63

DEPTH TO WATER IN BORING

DATE

SWN 266(C)
22 AUG 62