SWG Form 267
28 Jan 1965

PROJECT: G.I.W.W., Tributary Channel

LOCATION: Aransas Pass

Left

TEST DATA SUMMARY

BORING NO. 35T-8

DATE DRILLED Oct. 8, 1969

FIELD NO.	DEPTH	CLASSIFICATION ELEVATION TOP BORING _____	SYMBOL	CONSISTENCY	POCKET (1) PENETROMETER	STAN. PENET. BLOWS/FT (2)	MOISTURE CONTENT %	DRY DENSITY p.c.f.	L.L.	P.L.	BAR L.S.	SIEVE ANALYSIS PERCENT GRVL	SAND	FINES	INIT. WT.	ACC. WT. RTND. SIEVE NO. (3) NO. 4	NO. 10	NO. 40	NO. 200
	0-15.3	Water																	
J-1	15.3-17	Gray Silty Sand 15.3'-24'	SP-SM	M		9	26												
X	17-20	Driller's classification: Same as Above.																	
J-2	20-22	shell fragments 15.3'-24'		VD		25	25				0.0	0	94	6	50	0	0	0	47
X	22-24	Driller's classification: Same as Above.																	
C-1	24-27.5	Gr. Sandy Clay w/sand layers & shell frags. 24'-27.5'	CL	S	0.25		35	81	44		1.50	0	30	70	50	0	0	0	15
C-2	27.5-28	Gr. Clayey Sand w/shell frags. 27.5'-28'	SC	ST	1.00		21	103			6.0	0	76	24	50	0	0	1	38

BOTTOM AT 28'

WATER AT +15.3'

Tide 2.0 @ 0900hrs.

KEY: CONSISTENCY — COHESIVE SOILS: VS Very Soft, S Soft, M Medium, ST Stiff, VST Very Stiff, H Hard. CONSISTENCY — COHESIONLESS SOILS: VL Very Loose, L Loose, M Medium, D Dense, VD Very Dense.

(1) Tons/Sq.Ft. Unconfined Compressive Strength
(2) Split Barrel Sampler
(3) Acc. Wt. Rtnd ÷ Init. Wt. x 100 = % Rtnd.

BORING NO. 35T-8