

LOG OF BORING

Project : MTBE Improvement Areas-Tenneco Natural Gas Liquids Corp., La Porte, Texas
 Client : M.W. Kellogg Company
 Houston, Texas
 Boring No. : B-103
 File No. : 90-0422
 Date : 7-10-90
 Elevation : +18 ft.
 Dry Augered 0 to 30 ft. Water at Dry ft.; Caving at 18.6 ft.
 Wash Bored to ft. Water at 15.7 ft. after 24 hours

ELEV	SOIL SYMBOLS SAMPLER SYMBOLS AND FIELD TEST DATA	Description	Wc (%)	Dens. (pcf)	Qu or UU (tsf)	Str (%)	LL	PI	#200 (%)
DEPTH									
0	4.50	Very stiff-hard dark gray CLAY "FILL"	13				58	38	
	4.50	w/roots, shell & calcareous nodules	18						
	3.75	Very stiff gray & tan CLAY (CH)	18	109	2.15	3			
5	3.00	w/ferrous nodules	23						
	2.25	-w/many ferrous & calcareous nodules @ 4'-6'	26	105					
10	2.50	-stiff w/calcareous nodules below 8'							
	3.25	-very stiff below 13'							
15	3.75								
20	2.75	-stiff, reddish brown below 23'	29	90	1.55 (18)	4			
25	2.75								
30									

Bottom @ 30'