

<b>DRILLING LOG</b>	DIVISION Southwestern	INSTALLATION Galv Dist, Eng Div	SHEET OF SHEETS
1. PROJECT Wallisville Reservoir		10. SIZE AND TYPE OF BIT	
2. LOCATION (Coordinates or Station)		11. DATUM FOR ELEVATION SHOWN (TBM or MSL)	
3. DRILLING AGENCY Dept of the Army, GD, Corps of Engineers		12. MANUFACTURER'S DESIGNATION OF DRILL	
4. HOLE NO. (As shown on drawing title and file number) 3ST-341		13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN	DISTURBED UNDISTURBED 10 Cont
5. NAME OF DRILLER Black		14. TOTAL NUMBER CORE BOXES	
6. DIRECTION OF HOLE <input type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED _____ DEG. FROM VERT.		15. ELEVATION GROUND WATER	
7. THICKNESS OF OVERBURDEN		16. DATE HOLE	STARTED 30 Aug COMPLETED 30 Aug 1967
8. DEPTH DRILLED INTO ROCK		17. ELEVATION TOP OF HOLE	
9. TOTAL DEPTH OF HOLE 20.0		18. TOTAL CORE RECOVERY FOR BORING %	
		19. SIGNATURE OF INSPECTOR	

ELEVATION a	DEPTH b	LEGEND c	CLASSIFICATION OF MATERIALS (Description) d	% CORE RECOVERY e	BOX OR SAMPLE NO. f	REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) g
0.0	2.0		Gray clay w/roots, soft			Cont. 1 0.25
2.0	4.0		Gray clay, soft			Cont. 2 0.25
4.0	6.0		Gray clay w/sand seams, soft			Cont. 3 0.25
6.0	8.0		Gray sandy clay, v/soft			Cont. 4 0.0
8.0	10.0		Same as above, v/soft			Cont. 5 0.0
10.0	12.0		Same as above, v/soft			Cont. 6 0.0
12.0	14.0		Gray clay w/sand seams soft			Cont. 7 0.25
14.0	16.0		Gray clay w/org. mat. w/sand seams, v/soft			Cont. 8 0.0
16.0	18.0		Gray clay w/sand seams, soft			Cont. 9 0.25
18.0	20.0		Same as above, soft			Cont. 10 0.25
			BOTTOMED			
			Water table 0.0			