

DRILLING LOG		DIVISION Southwestern	INSTALLATION Galv Dist, Eng Div	SHEET OF SHEETS
1. PROJECT Wallisville Reservoir			10. SIZE AND TYPE OF BIT	
2. LOCATION (Coordinates or Station)			11. DATUM FOR ELEVATION SHOWN (TBM or MSL)	
3. DRILLING AGENCY U. S. Army Corps of Engineers			12. MANUFACTURER'S DESIGNATION OF DRILL	
4. HOLE NO. (As shown on drawing title and file number) 6ST-22			13. TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN: 2 Jars	UNDISTURBED 10 Cont
5. NAME OF DRILLER Watts <i>y = 740, 940</i> <i>x = 3,353, 180</i>			14. TOTAL NUMBER CORE BOXES	
6. DIRECTION OF HOLE <input type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED _____ DEG. FROM VERT.			15. ELEVATION GROUND WATER	
7. THICKNESS OF OVERBURDEN			16. DATE HOLE STARTED 5 May	
8. DEPTH DRILLED INTO ROCK			COMPLETED 5 May 1964	
9. TOTAL DEPTH OF HOLE 26.0			17. ELEVATION TOP OF HOLE = + 2.3'	
			18. TOTAL CORE RECOVERY FOR BORING %	
			19. SIGNATURE OF INSPECTOR	

ELEVATION a	DEPTH b	LEGEND c	CLASSIFICATION OF MATERIALS (Description) d	% CORE RECOVERY e	BOX OR SAMPLE NO. f	REMARKS (Drilling time, water loss, depth of weathering, etc., if significant) g
0.0	2.0		Brown clay, tree roots, org. medium to soft			Cont. 1 0.75 - 0.25
2.0	4.0		Dark gray clay, org. soft			Cont. 2 0.25
4.0	6.0		Same as above, v/soft			Cont. 3 T-Q 0.0
6.0	8.0		Dark gray clay, org., v/soft			Cont. 4 0.0
8.0	10.0		Same as above, v/soft			Cont. 5 T-R 0.0
10.0	12.0		Dark gray clay, v/soft			Jar 1
12.0	14.0		Same as above, v/soft			Cont. 6 0.0
14.0	16.0		Dark gray clay w/sand pockets v/soft			Cont. 7 D-S 0.0
16.0	18.0		Dark gray clay w/sand pockets v/soft			Cont. 8 Counsel 0.0
18.0	20.0		Same as above, no recovery			No sample
20.0	22.0		Gray clay sand pockets, shell frag, soft			Cont. 9 0.25
22.0	24.0		Gray sandy clay w/shell frag soft			Cont. 10 0.25
24.0	26.0		Gray clay, v/soft			Jar 2
			Bottomed Water - 1.1			