

LOG OF BORING

PROJECT: White Point Island Restoration
Nueces Bay - Corpus Christi, Texas

PROJECT NO. 1600-0159
BORING NO. B-6
DATE 9/20/2000
ELEV. NA

CLIENT: Shiner Moseley & Associates, Inc.
Corpus Christi, Texas

SHEET 1 of 1

FIELD DATA			LABORATORY DATA										DRILLING METHOD (S) :	
SOIL SYMBOL	DEPTH (FT)	SAMPLES	N: BLOWS/FT P: TONS/SQ.FT T: TONS/SQ.FT PERCENT RECOVERY/ ROCK QUALITY DESIGNATION	MOISTURE CONTENT	ATTEBERG LIMITS (%)			DRY DENSITY POUNDS/CU.FT	SHEAR STRENGTH (KIPS/SQ.FT)	FAILURE STRAIN (%)	CONFINING PRESSURE (POUNDS/SQ IN)	MINUS NO. 200 SIEVE (%)	GROUNDWATER INFORMATION:	
					LL	PL	PI						Depth of water from surface to mudline at time of drilling was 3.5 ft.	
													DESCRIPTION OF STRATUM	
			N=WH										No sample recovery, 0' to 2'.	
			N=WH	85									Clay, very soft, dark gray, with shell fragments and sand pockets. (CH)	
	5		T=.02		110	36	74							
			T=.03	103										
	10			44								16	Shell fragments, with sand, and some clay, gray.	
													TOTAL DEPTH = 10 FT (Below Mudline)	
	15													
	20													
N - STANDARD PENETROMETER TEST RESISTANCE P - POCKET PENETROMETER RESISTANCE T - POCKET TORVANE SHEAR STRENGTH													REMARKS:	
													PLATE 7	