



Aptim Environmental & Infrastructure, LLC

6401 Congress Avenue, Suite 140

Boca Raton, Florida 33487

Phone # 1-561-391-8102

Legend for Geotechnical Data

Grain Size Scale for Sediments

| Unified Soil Classification System (USCS) (ASTM D2487/2488) | | APTIM Standard Sieve Stack | | |
|--|---------------|----------------------------|------------|-----------|
| | | Sieve Number | Size (phi) | Size (mm) |
| Gravel | Coarse Gravel | 3/4 | -4.25 | 19.03 |
| | Fine Gravel | 5/8 | -4.00 | 16.00 |
| | | 7/16 | -3.50 | 11.20 |
| | | 5/16 | -3.00 | 8.00 |
| | | 3 1/2 | -2.50 | 5.60 |
| | | 4 | -2.25 | 4.75 |
| Sand | Coarse Sand | 5 | -2.00 | 4.00 |
| | | 7 | -1.50 | 2.80 |
| | | 10 | -1.00 | 2.00 |
| | Medium Sand | 14 | -0.50 | 1.40 |
| | | 18 | 0.00 | 1.00 |
| | | 25 | 0.50 | 0.71 |
| | | 35 | 1.00 | 0.50 |
| | Fine Sand | 45 | 1.50 | 0.36 |
| | | 60 | 2.00 | 0.25 |
| | | 80 | 2.50 | 0.18 |
| | | 120 | 3.00 | 0.13 |
| | | 170 | 3.50 | 0.09 |
| | | 200 | 3.75 | 0.08 |
| Fines | Silt/Clay | 230 | 4.00 | 0.06 |

Proportional Definition of Descriptive Terms

| <u>Descriptive Term</u> | <u>Range of Proportions</u> |
|-------------------------|-----------------------------|
| Sandy, gravelly, etc. | 35 % to 50 % |
| Some | 20 % to 35 % |
| Little | 10 % to 20 % |
| Trace | 1 % to 10 % |

Consistency of Cohesive Soils

| Description | Consistency Index | Approximate Undrained Shear Strength (kPa) | Field Identification |
|-------------|-------------------|--|--|
| Hard | | Over 300 | Indented with difficulty by thumbnail, brittle. |
| Very Stiff | >1 | 150-300 | Readily indented by thumbnail, still very tough. |
| Stiff | 0.75-1 | 75-150 | Readily indented by thumb but penetrated only with difficulty. Cannot be moulded in the fingers. |
| Firm | 0.5-0.75 | 40-75 | Can be penetrated several centimeters by thumb with moderate effort and moulded in fingers by strong pressure. |
| Soft | <0.5 | 20-40 | Easily penetrated several centimeters by thumb, easily moulded. |
| Very Soft | | Less than 20 | Easily penetrated several centimeters by fist, exudes between fingers when squeezed in fist. |

Source: *Engineering Properties of Soils and Rocks, Fourth Edition by Fred G. Bell*

USCS Classifications

Refers to the Army Corps of Engineers Unified Soils Classification System. Class types are defined primarily by grain size, sorting and percent of material passing the #200 sieve. Classification of materials on the core logs based on visual field examinations are identified on the core logs under the Classification of Materials Description. Classifications based on laboratory sieve analyses are identified on the core logs in the Legend and under Remarks.

| | | | | | |
|-------|--|--|-------|--|---|
| GW | | Well graded gravels or gravel-sand mixtures, little or no fines | ML | | Inorganic silts and very fine sands, rock flour, sandy silts or clayey silts with slight plasticity |
| GP | | Poorly graded gravels or gravel-sand mixtures, w/ little or no fines | MH | | Inorganic silts, micaceous or diatomaceous fine sandy or silty soil, elastic silts |
| GM | | Silty gravels, gravel-sand-silt mixtures | OL | | Organic silts and organic silt-clays of low plasticity |
| GC | | Clayey gravels, gravel-sand-clay mixtures | OH | | Organic clays of medium to high plasticity, organic silts |
| SW | | Well graded sands or gravelly sands, little or no fines | CL | | Inorganic clays of low to medium plasticity, gravelly clays, sandy clays, silty clays, lean clays |
| SP | | Poorly graded sands or gravelly sands, little or no fines | CH | | Inorganic clays of high plasticity, fat clays |
| SM | | Silty sands, sand-silt mixtures | PT | | Peat and other highly organic soils |
| SC | | Clayey sands, sand-clay mixtures | SP-SM | | Poorly-graded silty sand |
| SW-SM | | Well-graded silty sand | SM-SC | | Silty clayey sand |
| GW-GM | | Well-graded silty gravel | ML-CL | | Inorganic silty lean clay |
| GM-GC | | Clayey silty gravel | | | |

Note: Information is after ACOE Atlantic Division Manual # 1110-1-1 titled *Engineering and Design Geotechnical Manual for Surface and Subsurface Investigations*

| | | | | |
|--|--|-----------------|--|--------------------------------------|
| DRILLING LOG | | DIVISION | INSTALLATION | SHEET 1 OF 1 SHEETS |
| 1. PROJECT TX GLO Region 1 Recon Geotechnical Sand Search Jefferson, Chambers, Galveston and Brazoria Co. | | | 9. SIZE AND TYPE OF BIT 3.0 In. | |
| 2. BORING DESIGNATION TXGLO1-VC-23-072 | | | 10. COORDINATE SYSTEM/DATUM Texas State Plane South | |
| 3. DRILLING AGENCY APTIM | | | 11. MANUFACTURER'S DESIGNATION OF DRILL APTIM SEAS VC-700 Vibracore | |
| 4. NAME OF DRILLER APTIM | | | <input type="checkbox"/> AUTO HAMMER <input type="checkbox"/> MANUAL HAMMER | |
| 5. DIRECTION OF BORING <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED | | | 12. TOTAL SAMPLES 0 | |
| 6. THICKNESS OF OVERBURDEN 0.0 Ft. | | | 13. TOTAL NUMBER CORE BOXES | |
| 7. DEPTH DRILLED INTO ROCK 0.0 Ft. | | | 14. ELEVATION GROUND WATER | |
| 8. TOTAL DEPTH OF BORING 19.0 Ft. | | | 15. DATE BORING 10-16-23 | |
| | | | 16. ELEVATION TOP OF BORING -48.0 Ft. | |
| | | | 17. TOTAL RECOVERY FOR BORING 16.7 Ft. | |
| | | | 18. SIGNATURE AND TITLE OF INSPECTOR SM | |

| ELEV. (ft) | DEPTH (ft) | LEGEND | CLASSIFICATION OF MATERIALS Depths and elevations based on measured values | % REC. | BOX OR SAMPLE | REMARKS The USCS classification system defines silt as the percent passing the No.200 (0.075 mm) sieve |
|---------------|---------------|--------|---|-----------|------------------|--|
| -48.0 | 0.0 | | | | | |
| -53.3 | 5.3 | | LEAN CLAY, very soft, trace shell hash, trace silt, hardness increases with depth in layer, shell hash and silt distributed in laminae, 0.5" shell fragment @ 1.0', 1.25" silt pocket with shell hash @ 3.2', dark greenish gray (10Y-4/1), (CL). | | T1 | Sample #T1, Depth = 2.5' Ave. Field Vane (tsf): 0.00 |
| -57.8 | 9.8 | | FAT CLAY, hard, trace rock fragments, trace shell hash, shell hash decreases with depth in layer, (1.25" x 1.5") rock fragment @ 5.5', brown (7.5YR-4/4), (CH). | | T2 | Sample #T2, Depth = 7.5' Ave. Field Vane (tsf): 0.44 |
| -61.0 | 13.0 | | FAT CLAY, hard, possible bioturbation throughout layer, color is mottled olive gray (5Y 5/2) and brown (7.5YR-5/3), (CH). | | T3 | Sample #T3, Depth = 11.3' Ave. Field Vane (tsf): 0.51 |
| -64.0 | 16.0 | | FAT CLAY, very stiff, some sandy silt, sand component is fine grained quartz, sandy silt increases with depth in layer, brown (7.5YR-5/4), (CH). | | T4 | Sample #T4, Depth = 14.5' Ave. Field Vane (tsf): 0.31 |
| -64.7 | 16.7 | | Silty SAND, fine grained, quartz, yellowish brown (10YR-5/4), (SM). | | | |
| -67.0 | 19.0 | | No recovery. | | | |
| | | | End of Boring | | | |



Texas General
Land Office

Texas GLO
Region 1
Geotechnical
Reconnaissance
Survey

TXGLO1-VC-23-072

Date Collected: 10/16/23
Top Elev. (ft NAVD88): -48.0
Bottom Elev. (ft NAVD88): -64.7
Core Length (ft): 16.7



6401 Congress Avenue, Suite 140
Boca Raton, FL 33487
www.aptim.com
(561)391-8102



Mini Vane Shear Test Results

| CORE ID | SAMPLE DEPTH (ft) | TORVANE (kg/cm ²) | TORVANE (tsf) | TORVANE (kpa) | DESCRIPTION ¹ |
|------------------|----------------------|----------------------------------|------------------|------------------|--------------------------|
| TXGLO1-VC-23-071 | 2.0 | 0.3 | 0.03 | 24.52 | Soft |
| | 5.0 | 0.5 | 0.05 | 49.03 | Firm |
| | 6.4 | 2.5 | 0.26 | 245.17 | Very Stiff |
| | 7.4 | 5.0 | 0.51 | 490.33 | Hard |
| | 8.2 | 4.3 | 0.44 | 416.78 | Hard |
| | 9.0 | 3.5 | 0.36 | 343.23 | Hard |
| | 9.8 | 3.0 | 0.31 | 294.20 | Very Stiff |
| | 11.0 | 2.0 | 0.20 | 196.13 | Very Stiff |
| | 12.4 | 3.0 | 0.31 | 294.20 | Very Stiff |
| | 14.4 | 2.3 | 0.23 | 220.65 | Very Stiff |
| | 16.3 | 3.0 | 0.31 | 294.20 | Very Stiff |
| | 17.2 | 7.0 | 0.72 | 686.47 | Hard |
| TXGLO1-VC-23-072 | 2.5 | 0.0 | 0.00 | 0.00 | Very Soft |
| | 7.5 | 4.3 | 0.44 | 416.78 | Hard |
| | 11.3 | 5.0 | 0.51 | 490.33 | Hard |
| | 14.5 | 3.0 | 0.31 | 294.20 | Very Stiff |
| TXGLO1-VC-23-073 | 9.2 | 5.0 | 0.51 | 490.33 | Hard |
| TXGLO1-VC-23-074 | 0.5 | 0.0 | 0.00 | 0.00 | Very Soft |
| | 3.0 | 3.5 | 0.36 | 343.23 | Hard |
| | 5.5 | 5.8 | 0.59 | 563.88 | Hard |
| | 8.2 | 3.5 | 0.36 | 343.23 | Hard |
| | 14.0 | 8.0 | 0.82 | 784.53 | Hard |
| TXGLO1-VC-23-075 | 1.6 | 0.8 | 0.08 | 73.55 | Firm |
| | 13.4 | 0.5 | 0.05 | 49.03 | Firm |
| | 15.9 | 4.0 | 0.41 | 392.27 | Hard |
| | 17.1 | 2.5 | 0.26 | 245.17 | Very Stiff |
| TXGLO1-VC-23-076 | 0.8 | 0.3 | 0.03 | 24.52 | Soft |
| | 2.0 | 0.5 | 0.05 | 49.03 | Firm |
| | 3.6 | 1.0 | 0.10 | 98.07 | Stiff |
| | 6.5 | 2.0 | 0.20 | 196.13 | Very Stiff |
| | 13.4 | 5.0 | 0.51 | 490.33 | Hard |
| TXGLO1-VC-23-077 | 6.7 | 5.0 | 0.51 | 490.33 | Hard |
| | 12.6 | 4.0 | 0.41 | 392.27 | Hard |
| | 17.0 | 7.0 | 0.72 | 686.47 | Hard |
| TXGLO1-VC-23-078 | 3.0 | 2.0 | 0.20 | 196.13 | Very Stiff |
| | 6.7 | 4.5 | 0.46 | 441.30 | Hard |
| | 10.6 | 3.0 | 0.31 | 294.20 | Very Stiff |
| | 13.7 | 4.0 | 0.41 | 392.27 | Hard |
| | 16.5 | 5.5 | 0.56 | 539.37 | Hard |
| TXGLO1-VC-23-079 | 0.5 | 0.0 | 0.00 | 0.00 | Very Soft |
| | 1.2 | 1.0 | 0.10 | 98.07 | Stiff |
| | 3.5 | 3.5 | 0.36 | 343.23 | Hard |
| | 12.1 | 4.0 | 0.41 | 392.27 | Hard |
| TXGLO1-VC-23-080 | 0.1 | 0.0 | 0.00 | 0.00 | Very Soft |