

BORING LOG	DISTRICT	INSTALLATION	SHEET 1 OF 1 SHEETS
1. PROJECT Galveston Channel and Pelican Island PA		7. ELEVATION OF HOLE	
2. LOCATION (Coordinates or Station) N=13694586 E=3304160		8. DATUM FOR ELEVATION	
3. DRILLING AGENCY Dempsey (Geotest Engineering, Inc.)		9. ELEVATION OF GROUNDWATER ▽ TOD: ▼ 24-HR:	
4. LABORATORY TESTING AGENCY Tolunay-Wong Engineers, Inc.		10. DRILLING DATE and TIME STARTED: COMPLETED:	
5. DEPTH OF WATER ▽ TOD: ▼ 24-HR:		11. CLASSIFICATION REFERENCE	
6. DEPTH OF HOLE 6 ft		12. ENGINEER	

[illegible]

SUMMARY OF LABORATORY TESTS

Project No. 08.18.918

Client: United States Army Corps of Engineers

Project: Galveston Channel and Pelican Island PA

Contract No. DACW64-03-D-0008, Task Order No. 0077

Boring No.	Sample No.	Depth (ft)	Soil Description	USCS	Water Content (%)	Dry Density (pcf)	Liquid Limit	Plastic Limit	Plast. Index	Finer than #200 Sieve (%)	Lab Vane (tsf)	Uc/UU. Compr. (tsf)	Failure Strain (%)	Conf. Pres. (psi)	Failure Type
	1	0-2	Gray and tan FAT CLAY	CH	51.8	68.7									
	2	2-4	Gray and tan FAT CLAY	CH	43.0	74.7	85	24	61	93.4		0.65	3.4		Multiple shear
	3	4-6	Gray and tan FAT CLAY with SAND	CH	42.6	79.4									
	4	6-8	Gray and tan FAT CLAY with SAND	CH	44.2	75.9	67	22	45	84.7		0.53	4.9		45 degree
	5	8-10	Gray and tan FAT CLAY	CH	36.6	82.1									
	6	10-12	Gray and tan FAT CLAY	CH	39.9	75.8									
	7	12-14	Gray FAT CLAY	CH	44.5	71.9						0.45	3.8		45 degree
	8	14-16	Gray and tan FAT CLAY; sand pockets	CH	45.4	69.9	78	24	54	88.3		0.44	5.5		Multiple shear
	9	16-18	Gray and tan FAT CLAY	CH	38.5	84.2									
	10	18-20	Tan and light gray FAT CLAY; calcareous nodules	CH	31.7	84.0	74	23	51	97.8		1.14	11.5		Multiple shear
	11	20-22	Tan and light gray FAT CLAY	CH	34.7	83.1									
	12	22-24	Dark gray FAT CLAY	CH	64.1	62.3									
	13	24-26	Gray FAT CLAY	CH	51.3	66.5	71	22	49	99.0					Multiple shear
	14	26-28	Tan and gray FAT CLAY	CH	57.1	64.9									
	15	28-30	Gray and tan FAT CLAY	CH	59.4	61.6									
	16	30-32	Gray FAT CLAY	CH	61.8	59.6	90	25	65	91.0		0.33	4.3		60 degree
	17	32-34	Gray FAT CLAY; sand pockets	CH	25.2	96.1									
	18	34-35.5	Gray SILTY SAND	SM						26.6					
	19	36-38	Gray FAT CLAY; sand pockets	CH	56.3	61.7									
	20	38-40	Gray FAT CLAY	CH	44.0	74.9	56	20	36	85.3					Bulge
	21	40-42	Gray FAT CLAY; sand pockets	CH	42.7	77.4									
	22	42-43.5	Gray POORLY GRADED SAND with SILT	SP-SM						11.1					
	23	46-48	Gray and tan FAT CLAY; shell fragments	CH	21.8	103.2									
	24	48-50	Light gray and tan SANDY LEAN CLAY	CL	19.9	108.8									
07-183															
	1	0-1	Gray FAT CLAY	CH											
	2	1-2	Gray FAT CLAY; organics	CH	93.8		110	28	82	99.5					
	3	2-3	Gray and tan FAT CLAY	CH											
	4	3-4	Gray FAT CLAY	CH	60.6		86	24	62	97.9					
	5	4-5	Gray and tan FAT CLAY	CH											
	6	5-6	Gray and tan FAT CLAY	CH	77.1										
07-184															
	1	0-2	Gray FAT CLAY	CH	41.6	79.5									
	2	2-4	Gray and tan FAT CLAY with SAND	CH	39.5	76.7	90	25	65	73.7		0.38	4.7		45 degree
	3	4-6	Gray and tan FAT CLAY	CH	75.5	51.3									
	4	6-8	Gray FAT CLAY; organics	CH	66.0	56.9	108	28	80	98.0		0.29	8.2		45 degree
	5	8-10	Gray FAT CLAY	CH	78.9	56.5									

Our letters and reports are for the exclusive use of the CLIENT. This document shall not be reproduced, except in full, without our prior written approval.