

BORING LOG	DISTRICT	INSTALLATION	SHEET OF 1 SHEETS
1. PROJECT Galveston Channel and Pelican Island PA		7. ELEVATION OF HOLE	
2. LOCATION (Coordinates or Station) N=13691679 E=3304861		8. DATUM FOR ELEVATION	
3. DRILLING AGENCY Dempsey (Geotest Engineering, Inc.)		9. ELEVATION OF GROUNDWATER ▽ TOD: ▼ 24-HR:	
4. LABORATORY TESTING AGENCY Tolunay-Wong Engineers, Inc.		10. DRILLING DATE and TIME STARTED: COMPLETED:	
5. DEPTH OF WATER ▽ TOD: ▼ 24-HR:		11. CLASSIFICATION REFERENCE	
6. DEPTH OF HOLE 6 ft		12. ENGINEER	

[illegible]

SUMMARY OF LABORATORY TESTS

Project No. 08.18.918

Client: United States Army Corps of Engineers

Project: Galveston Channel and Pelican Island PA

Contract No. DACW64-03-D-0008, Task Order No. 0077

Boring No.	Sample No.	Depth (ft)	Soil Description	USCS	Water Content (%)	Dry Density (pcf)	Liquid Limit	Plastic Limit	Plast. Index	Finer than #200 Sieve (%)	Lab Vane (tsf)	Uc/UU. Compr. (tsf)	Failure Strain (%)	Conf. Pres. (psi)	Failure Type
	6	10-12	Gray FAT CLAY	CH	64.1	60.6									
	7	12-14	Tan and gray FAT CLAY	CH	48.3	69.5	79	24	55	92.8		0.36	3.4		45 degree
	8	14-16	Gray FAT CLAY	CH	63.6	65.0									
	9	16-18	Tan and gray FAT CLAY	CH	59.1	64.5	94	24	70	98.6		0.41	2.0		Slickensided
	10	18-20	Gray and tan FAT CLAY	CH	50.0										
07-185															
	1	0-1	Gray FAT CLAY	CH											
	2	1-2	Gray and tan FAT CLAY	CH	70.1		101	27	74	95.9					
	3	2-3	Gray FAT CLAY	CH											
	4	3-4	Tan and gray FAT CLAY	CH	77.9										
	5	4-5	Tan and gray FAT CLAY	CH											
	6	5-6	Tan and gray FAT CLAY	CH	65.8		94	26	68	99.1					
07-186															
	1	0-1	Tan and gray FAT CLAY	CH											
	2	1-2	Gray and tan FAT CLAY	CH	66.1		70	22	48	96.3					
	3	2-3	Gray and tan FAT CLAY	CH											
	4	3-4	Tan and light gray CLAYEY SAND	SC	33.8		43	18	25	43.3					
	5	4-5	Tan and gray FAT CLAY	CH											
	6	5-6	Gray and tan FAT CLAY	CH	70.1										
07-187															
	1	0-2	Gray and tan FAT CLAY	CH	43.7	73.8									
	2	2-4	Tan and gray FAT CLAY	CH	35.7	82.2									
	3	4-6	Gray FAT CLAY	CH	43.9	75.7	80	24	56	95.1		0.66	4.3		45 degree
	4	6-8	Gray and tan FAT CLAY	CH	44.4	75.0									
	5	8-10	Gray and tan FAT CLAY	CH	52.1	66.3	93	25	68	87.7		0.49	2.2		Slickensided
	6	10-12	Tan and light gray FAT CLAY	CH	36.3	81.2									
	7	12-14	Tan and light gray FAT CLAY	CH	33.9	84.8									
	8	14-16	Gray and tan FAT CLAY with SAND	CH	19.3	95.4	58	20	38	74.2		0.81	4.5		45 degree
	9	16-18	Gray and tan FAT CLAY with SAND	CH	18.4	109.6									
	10	18-20	Tan and light gray FAT CLAY	CH	35.4	87.3	64	21	43	92.0		0.84	8.1		Multiple shear
	11	20-22	Tan and light gray FAT CLAY; calcareous nodules	CH	31.5	88.6									
	12	22-24	Gray and tan FAT CLAY	CH	46.2	69.4									
	13	24-26	Dark gray and tan FAT CLAY	CH	54.5	66.7	107	28	79	98.7		0.89	2.2		Slickensided
	14	26-27.5	Gray and tan SANDY LEAN CLAY	CL	39.9										
	15	27-29.5	Gray and tan SILTY SAND	SM						40.9					
	16	32-34	Gray SILTY SAND	SM						29.9					
	17	34-36	Gray CLAYEY SAND	SC	29.6		27	15	12	46.5					

Our letters and reports are for the exclusive use of the CLIENT. This document shall not be reproduced, except in full, without our prior written approval.