

May 31, 2006
 Attn.: Mr. Hugo E. Bermudez, P.E.
 RETL Job No.: G106337

PROPOSED SAN LUIS PASS PROJECT
 West Galveston Bay
 Freeport, Texas

	BORING B-5				BORING B-6			
SIEVE SIZE	0-2.5'	2.5'-5'	5'-7.5'	7.5'-10'	0-2.5'	2.5'-5'	5'-7.5'	7.5'-10'
#10	100	100	100	100	100	100	100	100
#20	99	100	100	100	100	100	100	100
#40	98	100	100	100	100	100	100	99
#60	98	99	100	99	99	99	99	98
#70	97	98	99	98	98	98	98	97
#80	96	95	97	95	94	95	95	91
#100	73	76	80	74	58	74	55	49
#120	33	42	39	40	22	35	23	26
#140	12	21	15	18	9	16	9	15
#200	2.4	7.2	3.5	5.5	1.6	5.5	3.5	8.4
#230	1.9	5.8	3.4	4.5	1.3	5.5	3.1	7.4
Color	2.5Y 6/2	2.5Y 4/1	2.5Y 5/2	2.5Y 5/2	2.5Y 5/1	2.5Y 5/1	2.5Y 5/1	2.5Y 5/1
Description	Lt Brown Gray	Dark Gray	Gray Brown	Gray Brown	Gray	Gray	Gray	Gray

	BORING B-7					
SIEVE SIZE	0-2.5'	2.5'-5'	5'-7.5'	7.5'-10'	10'-12.5'	12.5'-15'
#10	100	100	100	99	100	100
#20	100	100	99	99	100	100
#40	100	100	99	98	100	100
#60	99	100	98	97	99	99
#70	99	100	97	94	99	99
#80	97	99	92	88	96	98
#100	44	87	47	55	79	82
#120	17	42	20	25	40	39
#140	7	15	8	9	17	16
#200	2.0	4.1	2.7	2.4	4.3	5.3
#230	1.8	3.6	2.5	2.1	1.3	4.7
Color	2.5Y 5/2	2.5Y 5/1	2.5Y 5/1	2.5Y 6/2	2.5Y 6/2	2.5Y 5/2
Description	Gray Brown	Gray Brown	Gray	Lt. Brown Gray	Lt. Brown Gray	Gray Brown

LOG OF BORING B-5

SHEET 1 of 1



Rock Engineering and Testing Laboratory, Inc.
4910 Neptune Street
Corpus Christi, Texas 78405
Telephone: (361) 883-4555
Fax: (361) 883-4711

CLIENT: Coast and Harbor Engineering, Inc.
PROJECT: Proposed San Luis Pass Project
LOCATION: W. Galveston Bay; Freeport, Texas
NUMBER: G106337

DATE(S) DRILLED: 5/18/06 - 5/18/06

FIELD DATA										LABORATORY DATA					DRILLING METHOD(S): Disturbed Samples
SOIL SYMBOL	DEPTH (FT)	SAMPLE NUMBER	SAMPLES	N: BLOWS/FT P: TONS/SQ FT T: TONS/SQ FT PERCENT RECOVERY/ ROCK QUALITY DESIGNATION	MOISTURE CONTENT (%)	ATTERBERG LIMITS			DRY DENSITY POUNDS/CU.FT	COMPRESSIVE STRENGTH (TONS/SQ FT)	MINUS NO. 200 SIEVE (%)	GROUNDWATER INFORMATION: N/A			
						LL	PL	PI							
												SURFACE ELEVATION: N/A			
												DESCRIPTION OF STRATUM			
												WATER DEPTH= 1-FOOT			
	1											POORLY GRADED SAND , 2.5Y 6/2 light brown gray. Same as above, 2.5Y 4/1 dark gray.			
	2	S-1									2				
	3										7				
	4	S-2													
	5											Same as above, 2.5Y 5/2 gray brown.			
	6										4				
	7	S-3													
	8														
	9											POORLY GRADED SAND , 2.5Y 5/2 gray brown.			
	10	S-4									6				
												Boring terminated at a depth of 10' below the bay bottom.			

N - STANDARD PENETRATION TEST RESISTANCE
P - POCKET PENETROMETER RESISTANCE
T - POCKET TORVANE SHEAR STRENGTH

REMARKS:

Soil Sampling performed by RETL at N29 deg 05' 39.2" W95 deg 08' 06.4"

