

Rock Engineering and Testing Laboratory, Inc. 4910 Neptune Street
Corpus Christi, Texas 78405
Telephone: (361) 883-4555
Fax: (361) 883-4711

P - POCKET PENETROMETER RESISTANCE T - POCKET TORVANE SHEAR STRENGTH

CLIENT: Pacific International Engineering, PLLC PROJECT:

Key Allegro Shoreline Stabilization

LOCATION: Rockport, Texas

NUMBER: C0200592

Fax: (361) 883-4711											DATE(S) DRILLED: 09/26/02 - 09/26/02
FIE		LABORATORY DATA							DRILLING METHOD(S): Hollow Stem Auger		
DEРТН (FT)	SAMPLE NUMBER	SAMPLES	N. BLOWS/FT P: TONS/SQ FT T: TONS/SQ FT PERCENT RECOVERY/ ROCK QUALITY DESIGNATION	MOISTURE CONTENT (%)		PLASTIC LIMIT IN THE		DRY DENSITY POUNDS/CU.FT	COMPRESSIVE STRENGTH (TONS/SQ FT)	MINUS NO. 200 SIEVE (%)	GROUNDWATER INFORMATION: Groundwater (GW) encountered at a depth of 1' during drilling operations. GW @ 2' and the boring caved at 2.5' immediately after completion of drilling opera
-	00 \	\s\/	Zarax	2	LL	PL	PI		0 % 5	2	DESCRIPTION OF STRATUM
-	SS S-1			17						10	POORLY GRADED SAND, with shell fragments, brown, moist, medium.
- 5	SS S-2		N= 8	16							Same as above, loose.
-	\$\$ \$-3		N= 5	23							Same as above, trace shell, very loose.
- 10 -	SS S-4		N= 8	23						3	POORLY GRADED SAND, some shell, gray, moist, loose.
-	SS S-5		N= 15	25							Same as above, medium.
- 15	SS S-6		N= 8	26							Same as above, loose.
20 -	SS S-7		N= 0	22						7	POORLY GRADED SAND, with shell fragments, gray, moist, very loose.  Boring was terminated at a depth of 20-feet.

