

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE NO.	PEN./TORVANE	SPT.-BLOW COUNT	BORING NO. <u>91-69</u> DATE: BEGIN <u>3-6-91</u> PAGE <u>1 / 1</u>				
JOB NO. <u>14G 446</u> COMPLETE <u>3-6-91</u> Thin Walled Tube ☒ 3" ☐ 6"									
PROJECT <u>CHANNEL TO VICTORIA</u>					LOCATION <u>VICTORIA CHANNEL</u>				
ELEVATION OF HOLE _____					MANUFACTURER'S DESIGNATION OF DRILL RIG <u>F-3L</u>				
GROUNDWATER: DEPTH <u>6</u> ft., ELEV. _____ ft., at end of Drilling					WEATHER <u>CLEAR & SUNNY</u>				
DRILLER <u>ROBERT TANKERLEY</u>					LOGGER <u>JOHN A. GENTRY</u>				
		COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS			
0									
	1	1.25	LIGHT GRAY	SAND	STIFF	Clayey	w/CLAY SEAMS 0'-8'		
	2	4.5+	"	CLAY	HARD	Very sandy	w/GRAVEL 2'-4'		
5	3	3.5	"	"	VERY STIFF	Sandy			
	4	4.5+	"	"	HARD	"			
	5	4.5+	LIGHT GRAY	CLAY	HARD	SANDY	*+TAN		
10	6	4.25	"	"	"	"			
	7		LIGHT GRAY	SAND			*+TAN		
15	8	15/28	"	"	DENSE				
	9	13/28	"	"	DENSE				
20	10	4.0	LIGHT GRAY	CLAY	VERY STIFF		*+TAN w/CALC NODS		
25	11	4.0	"	"	"				
	12	4.5+	LIGHT GRAY	CLAY	HARD	SANDY	*+TAN w/CALC NODS + SAND POCKETS		
30	13	4.0	"	"	Very stiff	"			
							Bottom of 91-69		
35									