

U.S. ARMY CORPS OF ENGINEERS

BKM

DEPTH, FEET		SAMPLE NO.	PEN./TORVANE	SPT.-BLOW COUNT	BORING NO. <u>91-26</u> DATE: BEGIN <u>03-13-91</u> PAGE <u>112</u>				
					JOB NO. <u>146446</u> COMPLETE <u>03-13-91</u> Thin Walled Tube				
					PROJECT <u>CHANNEL TO VICTORIA</u> ☒ 3" ☐ 6"				
					LOCATION <u>VICTORIA CHANNEL</u>				
					ELEVATION OF HOLE _____				
					MANUFACTURER'S DESIGNATION OF DRILL RIG <u>F36</u>				
					GROUNDWATER: DEPTH <u>5</u> ft., ELEV. _____ ft., at end of Drilling				
					WEATHER _____				
					DRILLER <u>ROBERT TANKERLEE</u> LOGGER <u>JOHNA GENTRY</u>				
					COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
0									
	1	1.25	GRAY	CLAY	STIFF				-w/ROOTS 0'-2
	2	4.25	"	"	HARD				
5	3	3.25	"	"	W/STIFF				
	4	1.25	"	"	STIFF				
	5	1.25	"	"	"				
10	6	1.25	"	"	"				
	7	1.0	"	"	MED				
15	8	0.75	GRAY	"	MEDIUM STIFF				+ TAN
	9	0.75	"	"	"				
	10	0.25			soft				
20	11	0.5	GRAY	CLAY	MEDIUM STIFF	SANDY			-w/SAND LAYERS
	12	0.25	"	"	SOFT	VARIES SANDY			+SHELL FRAGMENT 20-30
25	13	0.25	"	"	"	"			
	14	0.5	"	"	MEDIUM STIFF	"			
	15	0.75	"	"	"	"			
30	16	1.0	GRAY	CLAY	STIFF				-w/SHELL FRAGMENTS 30'
	17	1.5	"	"	STIFF				
35	18	1.5	LGH GRAY	"	"				+ TAN -w/SAND SEAMS +SHELL FRAGMENTS

U.S. ARMY CORPS OF ENGINEERS

BKM

DEPTH, FEET	SAMPLE	SAMPLE NO.	PEN./TORVANE SPT.-BLOW COUNT	BORING NO. <u>91-26</u> DATE: BEGIN <u>03-13-91</u> PAGE <u>2 1 2</u>				
				JOB NO. <u>14G 446</u> COMPLETE <u>03-13-91</u> Thin Walled Tube ☒ 3" ☐ 6"				
				PROJECT <u>CHANNEL TO VICTORIA</u>				
				LOCATION <u>VICTORIA CHANNEL</u>				
				ELEVATION OF HOLE _____				
				MANUFACTURER'S DESIGNATION OF DRILL RIG <u>F-36</u>				
				GROUNDWATER: DEPTH <u>5</u> ft., ELEV. _____ ft., at end of Drilling				
				WEATHER _____				
				DRILLER <u>ROBERT TANKERLEY</u> LOGGER <u>JOHN A. GENTRY</u>				
				COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
35		19	1.25	LEIGHT GRAY	CLAY	STIFF		-W/SAND GRAINS & SHELL FRAGMENTS
40		20	1.25	"	"	"		
								BOTTOM 9126
45								
50								
55								
60								
65								
70								