VICTORIA CHANNEL

LOG OF BORING NO. 3ST-151

TYPE: 3" SHELBY TUBE

LOCATION: Sta. 1737

DEPTH FT	SYMBOL	SAMPLES	DESCRIPTION OF MATERIAL (SURF EL)	BLOWS PER FT	UNIT DRY WT LBS / CU FT
	CH		Dark Gray - Brown Clay Hard - V/Stiff	9.5	
			L.S.=31.5 0-2-98	98.3	
5				98	
			Calcareous Nodules	100.1	
				100.6	
10	CL		Buff Gray Clay V/Stiff Sandy 18'-19'	100.8	
				98.6	
15			L.S.=16.5 0-2-98	101.7	
				103	
	GP GM		Silty Sandy Gravel 2-30-68 58-93-5		
20	GP		Sandy Gravel 77-21-2		
25	GW		Sandy Gravel Dense 24 78-19-3		
30	GP GM		Silty Sandy Gravel 55-37-6		
	GM		Silty Sandy Gravel 40-36-24		
35	GP		Silty Sandy Gravel 74-18-8		
			75-15-10		
	GM		80-11-7		
40	GC		Gray, Clayey Sandy Gravel L.S.=11.0 49-24-27		
	CL		Gray Sandy Clay L.S.=7.0 0-96-59	100.5	
45	SM SP		Gray, Silty Sand 4-98-8		
	CL		Gray Sandy Clay 7-28-64 L.S.=10.0		
	SM		Gray Silty Sand 0-76-24		
50					

POCKET PENETROMETER TONS / SQ. FT: 0.5, 1.0, 1.5, 2.0, 2.5, 3.0

PLASTIC LIMIT — WATER CONTENT, % — LIQUID LIMIT: 10, 20, 30, 40, 50, 60

ELEVATION FT: 26.6

COMPLETION DEPTH 50.0

DATE 17 June 63

DEPTH TO WATER IN BORING 12.6

DATE

SWN-266(C)
22 AUG 63