

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE	SAMPLE NO.	PEN./TORVANE SPT.-BLOW COUNT	BORING NO. <u>E3-17</u> DATE: BEGIN <u>10-17-02</u> PAGE <u>111</u> JOB NO. <u>1140127279</u> COMPLETE <u>10-17-02</u> Thin Walled Tube PROJECT <u>Lost Lake Placement Area</u> ☒ 3" ☐ 6" LOCATION <u>X=3,242,894.9210</u> <u>Y=725,609.7081</u> ELEVATION OF HOLE <u>19.41</u> MANUFACTURER'S DESIGNATION OF DRILL RIG <u>CF-1000 Marsh Buggy</u> GROUNDWATER: DEPTH <u>2</u> ft., ELEV. _____ ft., at end of Drilling WEATHER <u>SUNNY</u> DRILLER <u>Dempsey Locarelli</u> LOGGER <u>John A. Gentry</u>				
		COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS			
0	J	1	LT BROWN + GRAY	SAND	V. LOOSE	SILT	- W/ROOTS + CLAY SMS 0-1'		
		2	0.00 BROWN + GRAY	CLAY	V. SOFT				
		3	0.00 DARK GRAY	CLAY	V. SOFT		- W/HYDROCARBON ODOR 2-4'		
		4	0.00 GRAY	CLAY	V. SOFT		- W/SAND SMS		
5		5	0.00 GRAY + BROWN	CLAY	V. SOFT		- W/ SAND SMS		
	X	6	236 GRAY	SAND	M. DENSE	SILT			
10	X	7	WOM 1/6" DARK GRAY	SAND	V. LOOSE	SILT	- W/CLAY SMS		
	X	8	112 GRAY	SILT	V. LOOSE				
15	X	9	121 GRAY	SILT	V. LOOSE				
		10	0.00 DARK GRAY	CLAY	V. SOFT		* DARK GRAY CLAY 16'		
		11	0.00 DARK GRAY	CLAY	V. SOFT		- W/HYDROCARBON ODOR 16-22		
20		12	0.00 DARK GRAY + GRAY	CLAY	V. SOFT				
25									
30							J = JAR SAMPLE		
35							WOM = WEIGHT OF HAMMER		