

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE NO.	PEN./TORVANE	SPT.-BLOW COUNT	COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
BORING NO. <u>E1-09</u> DATE: BEGIN <u>10-21-02</u> PAGE <u>1/1</u>					JOB NO. <u>1140127279</u> COMPLETE <u>10-21-02</u> Thin Walled Tube				
PROJECT <u>Lost Lake placement Area</u>					☒ 3" ☐ 6"				
LOCATION <u>X= 3243 409.4144 Y=727 730.1942</u>					ELEVATION OF HOLE <u>18.25</u>				
MANUFACTURER'S DESIGNATION OF DRILL RIG <u>Pontoon mounted - Marsh Buggy</u>					GROUNDWATER: DEPTH <u>1</u> ft., ELEV. <u> </u> ft., at end of Drilling				
WEATHER <u>CLOUDY</u>					DRILLER <u>Dempsey Green</u> LOGGER <u>John A. Gentry</u>				
0		1	0.00		BROWN & GRAY	CLAY	V. SOFT		- W/ROOTS & SAND SMS
	J	2			GRAY & BROWN	SAND	V. LOOSE	SILT	
5	X	3	W.O.H. 1/6"		GRAY	SAND	V. LOOSE	SILT	
		4	0.00		GRAY & BROWN	CLAY	V. SOFT		- W/ SAND SMS ON TOP 6'
		5	0.00		GRAY & BROWN	CLAY	V. SOFT		
10		6	0.00		GRAY & BROWN	CLAY	V. SOFT		- W/ SAND SMS
		7	0.00		GRAY & BROWN	CLAY	V. SOFT		- W/ SAND SMS
15	J	8			GRAY	SAND	V. LOOSE	SILT	
		9	0.00		DARK GRAY	CLAY	V. SOFT		X DARK GRAY CLAY w/ 1/4" HYDRO CARBON 02/12/02 16-22
20	J	10	0.00		CLAY	CLAY	V. SOFT		SAMPLES BULDCR 18-22
	J	11	0.00		CLAY	CLAY	V. SOFT		
25									
30									J = JAR SAMPLE
35									