

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE NO.	PEN./TORVANE	SPT.-BLOW COUNT	BORING NO. <u>E3-02</u>	DATE: BEGIN <u>10/5-02</u>	PAGE <u>1/1</u>		
					JOB NO. <u>1140127279</u>	COMPLETE <u>10/5-02</u>	Thin Walled Tube ☒ 3" ☐ 6"		
					PROJECT <u>Lost Lake Placement Area</u>				
					LOCATION <u>X=3,243,631.5612, Y=725,750.6379</u>				
					ELEVATION OF HOLE <u>30.49</u>				
					MANUFACTURER'S DESIGNATION OF DRILL RIG <u>CF-1000 Marsh Buggy</u>				
					GROUNDWATER: DEPTH <u>14</u> ft., ELEV. _____ ft., at end of Drilling				
					WEATHER <u>SUNNY & WINDY</u>				
					DRILLER <u>Dempsey Gearen</u>	LOGGER <u>John A. Gentry</u>			
					COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
0	1	1.25	REDDISH BROWN GRAY	CLAY	STIFF				
	2	1.50	REDDISH BROWN GRAY	CLAY	STIFF				
5	3	2.50	REDDISH BROWN GRAY	CLAY	V. STIFF				
	4	3.50	REDDISH BROWN GRAY	CLAY	V. STIFF				
	5	2.25	REDDISH BROWN GRAY	CLAY	V. STIFF				
10	6	1.25	REDDISH BROWN GRAY	CLAY	V. STIFF				
	7	0.75	REDDISH BROWN GRAY	CLAY	M. STIFF				
15	J 8		GRAY	SAND	M. DENSE	SILT			
	X 9	5.58	GRAY	SAND	M. DENSE	SILT			
	X 10	6.79	GRAY	SAND	M. DENSE	SILT			
20	X 11	8.10	GRAY	SAND	M. DENSE	SILT			
	X 12	7.912	GRAY	SAND	M. DENSE	SILT			
25	X 13	7.1014	GRAY	SAND	M. DENSE	SILT			
	X 14	6.1012	GRAY	SAND	M. DENSE	SILT			
	15	0.00	DARK GRAY	CLAY	V. SOFT				
30	16	0.00	DARK GRAY	CLAY	V. SOFT				
	17	0.25	DARK GRAY	CLAY	SOFT				
35									

HOLE KEPT JUELING 012

DARK GRAY CLAY w/ 28 - w/ SAND & MS

J = JAR SAMPLE