

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE NO.	SAMPLE NO.	PEN./TORVANE SPT.-BLOW COUNT	BORING NO. <u>E3-13</u>	DATE: BEGIN <u>10-17-02</u>	PAGE <u>1/1</u>		
					JOB NO. <u>1140127279</u>	COMPLETE <u>10-17-03</u>	Thin Walled Tube		
					PROJECT <u>Lost Lake Placement Area</u>	☒ 3" ☐ 6"			
					LOCATION <u>X=3243,091.3584</u>	<u>Y=725.647,2894</u>			
					ELEVATION OF HOLE <u>20.81</u>				
					MANUFACTURER'S DESIGNATION OF DRILL RIG <u>CF-1000 Marsh Buggy</u>				
					GROUNDWATER: DEPTH <u>2</u> ft., ELEV. _____	ft., at end of Drilling			
					WEATHER <u>SUNNY</u>				
					DRILLER <u>Dempsey Gearen</u>	LOGGER <u>John A. Gentry</u>			
					COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
0		J 1			GRAY + Lt Brown	SAND	V. LOOSE	SILT	-W/ROOTS + CLAY SMS
		X 2	1.1		GRAY	SAND	V. LOOSE	SILT	
5		X 3	1.34		GRAY + Lt Brown	SAND	LOOSE	SILT	
		4	0.50		Brown + CLAY	CLAY	M. STIFF		
		5	0.00		Brown + CLAY	CLAY	V. SOFT		-W/ SILT SMS
10		X 6	4.56		GRAY	SAND	M. DENSE		
		7	0.00		DARK GRAY + GRAY	CLAY	V. SOFT		-W/ HYDROCARBON DARK 12-14
15		J 8			GRAY	SILT	M. DENSE	SAND	
		X 9	4.34		GRAY	SAND	M. DENSE	SILT	
		10	0.00		DARK GRAY	CLAY	V. SOFT		*DARK GRAY CLAY 2018 -W/ HYDROCARBON DARK 18-22
20		J 11	0.00		DARK GRAY	CLAY	V. SOFT		SAMPLE BULGE 20-22
		12	0.00		DARK GRAY	CLAY	V. SOFT		
25									
30									
35									

J = JAR SAMPLE