

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE NO.	PEN./TORVANE	SPT.-BLOW COUNT	COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
BORING NO. <u>E2-01</u> DATE: BEGIN <u>10-18-02</u> PAGE <u>1/1</u>					JOB NO. <u>1140127279</u> COMPLETE <u>10-18-02</u> Thin Walled Tube				
PROJECT <u>Lost Lake Placement Area</u>					☒ 3" ☐ 6"				
LOCATION <u>X=3,243,613.067, Y=726,372.711</u>					ELEVATION OF HOLE				
MANUFACTURER'S DESIGNATION OF DRILL RIG <u>CF-1000 Marsh Buggy</u>					GROUNDWATER: DEPTH _____ ft., ELEV. _____ ft., at end of Drilling				
WEATHER <u>PARTLY CLOUDY</u>					DRILLER <u>Dempsey Gearen</u> LOGGER <u>John A. Gentry</u>				
0		1	0.75	REDDISH BROWN + GRAY	CLAY	M. STIFF			
		2	0.00	BROWN GRAY + DARK GRAY	CLAY	V. SOFT			W/ SAND SMS
5		3	0.75	GRAY + BROWN	CLAY	M. STIFF			W/ SAND + SILT SMS
		4	0.25	GRAY + BROWN	CLAY	SOFT			W/ SAND SMS
10		5	1.00	REDDISH BROWN + GRAY	CLAY	STIFF			
		6	1.50	REDDISH BROWN + GRAY	CLAY	STIFF			W/ Calc Nodules
		J 7		GRAY	SAND	Loose	Silt		
15		8	0.00	GRAY	CLAY	V. SOFT			W/ SILT SMS
		J 9	0.00	DARK GRAY	CLAY	V. SOFT			DARK GRAY CLAY w/ IL SAMPLE BULPGE
		10	0.00	DARK GRAY	CLAY	V. SOFT			W/ HYDROCARBON OPAR 16-22
20		11	0.00	DARK GRAY	CLAY	V. SOFT			
25									
30									J = JARSAMPLE
35									