SWG Form 267(C)
28 Jan 1965

PROJECT: P.A.C.C.W.W.

LOCATION: Channel to La Quinta

TEST DATA SUMMARY

BORING NO. 3st-27

DATE DRILLED 23 Feb 1965

FIELD NO.	DEPTH	CLASSIFICATION ELEVATION TOP BORING _____	SYMBOL	CONSISTENCY	POCKET (1) PENETROMETER	STAN. PENET. BLOWS/FT (2)	MOISTURE CONTENT %	DRY DENSITY P. c. f.	L.L.	P.L.	BAR L.S.	SIEVE ANALYSIS PERCENT GRVL	SAND	FINES	INIT. WT.	ACC. WT. RTND. SIEVE NO. (3) NO. 4	NO. 10	NO. 40	NO. 200
	0-33	Water																	
C-1	33-35	BROWN SANDY CLAY 33° TO 40°	CL	VS	2.0		22	102			9.6	0.0	34	66	50	0.0	0.0	0.5	17.0
C-2	35-37½	W/CAL NOD		ST	1.5														
C-3	37½-40			ST	1.0														
C-4	40-42½	BROWN SILTY SAND 40° TO 42½	SM	ST	1.5		12	116			0.0	6	60	34	50	3.0	7.0	11.0	33.0
J-1	42½-44	BROWN GRAVELLY SAND 42½ TO 44°	GP	D		25	16				0.0	40	56	4	50	20.0	32.0	37.0	48.0
X	44-47	GRAY CLAY W/CAL NOD 44° TO 52°	CH																
C-5	47-49½			VST	3.75		25	98	53		15.0	0.0	14	86	50	0.0	0.0	0.0	7.0
C-6	49½-52			VST	3.0														
		J-1 40% CA/C Nod.																	

KEY: CONSISTENCY — COHESIVE SOILS: VS Very Soft, S Soft, M Medium, ST Stiff, VST Very Stiff, H Hard

CONSISTENCY — COHESIONLESS SOILS: VL Very Loose, L Loose, M Medium, D Dense, VD Very Dense

(1) Tons/Sq.Ft. Unconfined Compressive Strength
(2) Split Barrel Sampler
(3) Acc. Wt. Rtnd ÷ Init. Wt. x 100 = % Rtnd.

BORING NO. 3st-27