

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE NO.	PEN./TORVANE	SPT.-BLOW COUNT	BORING NO. <u>F3-22</u> DATE: BEGIN <u>10-17-02</u> PAGE <u>1/1</u>				
					JOB NO. <u>1140127279</u> COMPLETE <u>10-17-02</u> Thin Walled Tube				
					PROJECT <u>Lost Lake Placement Area</u> ☒ 3" ☐ 6"				
					LOCATION <u>X=3,242,649 3743</u> <u>Y=725,562 7314</u>				
					ELEVATION OF HOLE <u>18.73</u>				
					MANUFACTURER'S DESIGNATION OF DRILL RIG <u>CF-1000 Marsh Buggy</u>				
					GROUNDWATER: DEPTH <u>2</u> ft., ELEV. _____ ft., at end of Drilling				
					WEATHER <u>SUNNY</u>				
					DRILLER <u>Dempsey Gacaren</u> LOGGER <u>John A. Gentry</u>				
					COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
0		1	0.00		Brown	CLAY	V. SOFT		-W/ROOTS
		2	0.00		Brown + Dark Gray	CLAY	V. SOFT		
5		3	0.00		Brown	CLAY	V. SOFT		
		4	0.00		Gray + Brown	SAND	V. LOOSE	SILT	-W/CLAY SMLA
		5	0.00		Gray + Brown	CLAY	V. SOFT		-W/SILT LAYER
10		6			Brown + Gray	SAND	V. LOOSE	SILT	
		7	1/2		Gray	SILT	V. LOOSE	SAND	
15		8	0.00		DARK GRAY	CLAY	V. SOFT		* DARK GRAY CLAY w/ 1/4
		9	0.00		DARK GRAY	CLAY	V. SOFT		-W/HYDROCARBON OIL 14.20
		10	0.00		DARK GRAY + GRAY	CLAY	V. SOFT		
20									
25									
30									
35									