

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET	SAMPLE NO.	PEN./TORVANE	SPT.-BLOW COUNT	BORING NO. <u>EIA-02</u> DATE: BEGIN <u>10-21-02</u> PAGE <u>1/1</u>				
				JOB NO. <u>1140127279</u> COMPLETE <u>10-21-02</u> Thin Walled Tube				
PROJECT <u>Lost Lake Placement Area</u>				☒ 3" ☐ 6"				
LOCATION <u>X=3,243,304.217, Y=727,267.111</u>				ELEVATION OF HOLE				
MANUFACTURER'S DESIGNATION OF DRILL RIG <u>Pontoon mounted - Marsh Buggy</u>				GROUNDWATER: DEPTH <u>2</u> ft., ELEV. <u> </u> ft., at end of Drilling				
WEATHER <u>Cloudy</u>				DRILLER <u>Dempsey Green</u> LOGGER <u>John A. Gentry</u>				
				COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
0								
	1	10.00		Brown + GRAY	CLAY	V. SOFT		W/ROOTS + SILT SMS
	2			Brown + GRAY	SAND	V. LOOSE	SILT	
	3			GRAY	SAND	V. LOOSE	SILT	
5	4			Brown + GRAY	SILT	V. LOOSE		
	5	0.25		GRAY	CLAY	SOFT		
	6	0.25		Brown + GRAY	CLAY	SOFT		W/SAND ON BOTTOM 10
10	7			GRAY	SAND	LOOSE		
	8	2.34		GRAY	SAND	LOOSE		
15	9	0.00		DARK GRAY	CLAY	V. SOFT		*DARK GRAY CLAY w/ 14
	10	0.00		DARK GRAY	CLAY	V. SOFT		w/ HYDRO CARBON OPAR 14-20
	11	0.00		DARK GRAY	CLAY	V. SOFT		
20								
25								
30								
35								

GEOTEST ENGINEERING, INC.