

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE NO.	PEN./TORVANE	SPT.-BLOW COUNT	BORING NO. <u>E2-02</u> DATE: BEGIN <u>10-18-02</u> PAGE <u>111</u>					
					JOB NO. <u>1140127279</u> COMPLETE <u>10-18-02</u> Thin Walled Tube					
					PROJECT <u>Lost Lake Placement Area</u> ☒ 3" ☐ 6"					
					LOCATION <u>X=3,243,559.929, Y=726,372.526</u>					
					ELEVATION OF HOLE _____					
					MANUFACTURER'S DESIGNATION OF DRILL RIG <u>CF-1000 Marsh Buggy</u>					
					GROUNDWATER: DEPTH _____ ft., ELEV. _____ ft., at end of Drilling					
					WEATHER <u>PARTLY CLOUDY</u>					
					DRILLER <u>Dempsey Gearen</u> LOGGER <u>John A. Gentry</u>					
		COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS				
0	1	2.75	REDDISH BROWN CLAY	CLAY	U.S. STIFF		-w/ROOTS & SAND SMS ON TOP			
	2	1.25	REDDISH BROWN CLAY	CLAY	STIFF		-w/Calc Nods			
5	3	1.00	REDDISH YELLOWISH BROWN CLAY	CLAY	STIFF					
	4	2.50	REDDISH BROWN CLAY	CLAY	U.S. STIFF		-w/SAND SMS			
	5	0.75	REDDISH BROWN CLAY	CLAY	M. STIFF		-w/Calc Nods			
10	6	0.75	REDDISH BROWN CLAY	CLAY	M. STIFF		-w/SAND SMS			
	7	1.00	REDDISH BROWN CLAY	CLAY	STIFF		-w/Calc Nods & SAND SMS			
15	8	1.25	REDDISH BROWN CLAY	CLAY	STIFF		w/SAND SMS - m. 16			
	9		GRAY SAND		SILT		-w/ SAND ON TOP 18'-18'3"			
	10	0.75	GRAY CLAY	M. STIFF						
20	X11	4.56	GRAY SAND	M. DENSE	SILT					
	X12	5.77	GRAY SILT	M. DENSE	SAND					
25	13	0.25	GRAY CLAY	SOFT						
	14	0.50	GRAY CLAY	M. STIFF			-w SAND SMS			
	15		GRAY SAND							
30	16	0.50	REDDISH BROWN CLAY	M. STIFF			* DARK GRAY CLAY @ 30'			
	17	1.50	DARK GRAY CLAY	STIFF			-w/ SAND SMS			
	18	1.50	DARK GRAY CLAY	STIFF			-w/ HYDROCARBON @ PAR 30-36'			
35							-w/ SILT SMS			
							JE JAR SAMPLE			