

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE NO.	PEN./TORVANE	SPT.-BLOW COUNT	COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
BORING NO. <u>E2-03</u> DATE: BEGIN <u>10-18-02</u> PAGE <u>111</u> JOB NO. <u>1140127279</u> COMPLETE <u>10-18-02</u> Thin Walled Tube PROJECT <u>Lost Lake Placement Area</u> ☒ 3" ☐ 6" LOCATION <u>X=3,243,499.162, Y=726,370.645</u> ELEVATION OF HOLE _____ MANUFACTURER'S DESIGNATION OF DRILL RIG <u>CF-1000 Marsh Buggy</u> GROUNDWATER: DEPTH _____ ft., ELEV. _____ ft., at end of Drilling WEATHER <u>PARTLY CLOUDY</u> DRILLER <u>Dempsey Gearen</u> LOGGER <u>John A. Gentry</u>									
0	J1				BROWN GRAY	SAND	V. LOOSE		-w/ CLAY BALL
	2	0.00			REDDISH BROWN + GRAY	CLAY	V. SOFT		
5	3	0.00			BROWN GRAY	CLAY	V. SOFT		
	4				GRAY	SILT	LOOSE		
	X5	123			GRAY + BROWN	SILT	LOOSE	SAND	-w/ CLAY SMS
10	X6	234			GRAY	SAND	LOOSE	SILT	
	7	0.00			DARK GRAY	CLAY	V. SOFT		-w/ SAND SMS
15	8	1.00			REDDISH BROWN + GRAY	CLAY	STIFF		
	9	1.50			REDDISH BROWN + GRAY	CLAY	STIFF		
	10	1.25			REDDISH BROWN + GRAY	CLAY	STIFF		
20	11	0.00			REDDISH BROWN + GRAY	CLAY	V. SOFT		
	12	0.00			DARK GRAY	CLAY	V. SOFT		*DARK GRAY @ 22 -w/ HYDROCARBON ODA 22-28
25	13	0.25			DARK GRAY	CLAY	SOFT		
	14	0.25			DARK GRAY + GRAY	CLAY	SOFT		-w/ SILT SMS
30									
35									