

**U.S. ARMY CORPS OF ENGINEERS**

DEPTH, FEET	SAMPLE NO.	SAMPLE NO.	PEN./TORVANE	SPT.-BLOW COUNT	BORING NO. <u>S1-05</u> DATE: BEGIN <u>10-10-02</u> PAGE <u>111</u>				
					JOB NO. <u>1140127279</u> COMPLETE <u>10-10-02</u> Thin Walled Tube				
					PROJECT <u>Lost Lake Placement Area</u> <input checked="" type="checkbox"/> 3" <input type="checkbox"/> 6"				
					LOCATION <u>X=3,241,641.575, Y=724,036.639</u>				
					ELEVATION OF HOLE _____				
					MANUFACTURER'S DESIGNATION OF DRILL RIG <u>CF-1000 Marsh Buggy</u>				
					GROUNDWATER: DEPTH <u>4</u> ft., ELEV. _____ ft., at end of Drilling				
					WEATHER <u>CLOUDY</u>				
					DRILLER <u>Dempsey Coaren</u> LOGGER <u>John A. Gentry</u>				
					COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
0					1 1.25 REDDISH BROWN + GRAY	CLAY	STIFF		-w/ROOTS, SANDS, SMS, SHELL FRAG.
					2 1.00 REDDISH BROWN + GRAY	CLAY	STIFF		-w/SAND SMS & SHELL FRAG.
-5-					3 0.25 REDDISH BROWN + GRAY	CLAY	SOFT		-w/SAND SMS & SHELL FRAG.
					4 0.00 REDDISH BROWN + GRAY	CLAY	V.SOFT		-w/SAND SMS & SHELL FRAG.
					5 5 GRAY	SAND	V.LOOSE		
					6 0.00 REDDISH BROWN + GRAY	CLAY	V.SOFT		-w/SAND SMS & SHELL FRAG.
-10-					7 0.00 DARK GRAY	CLAY	V.SOFT		* DARK GRAY CLAY @ 10'
					8 0.00 DARK GRAY	CLAY	V.SOFT		-w/HYDROCARBON OIL @ 10-16'
-15-					9 0.00 DARK GRAY	CLAY	V.SOFT		-w SILT SMS
-20-									
-25-									
-30-									
-35-									