

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE NO.	PEN./TORVANE	SPT.-BLOW COUNT	COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
BORING NO. <u>E3-04</u> DATE: BEGIN <u>10-16-02</u> PAGE <u>111</u>					JOB NO. <u>1140127279</u> COMPLETE <u>10-16-02</u> Thin Walled Tube				
PROJECT <u>Lost Lake Placement Area</u>					☒ 3" ☐ 6"				
LOCATION <u>X = 3,243,533.3425, Y = 725,731.8473</u>					ELEVATION OF HOLE <u>22.89</u>				
MANUFACTURER'S DESIGNATION OF DRILL RIG <u>CF-1000 Marsh Buggy</u>					GROUNDWATER: DEPTH <u>2</u> ft., ELEV. _____ ft., at end of Drilling				
WEATHER <u>SUNNY</u>					DRILLER <u>Dempsey Coenen</u> LOGGER <u>John A. Gentry</u>				
0	1	1	0.75		REDISH BROWN + GRAY	CLAY	M. STIFF		-W/ROOTS SAND SAND SHELLS
	5	2			GRAY + BROWN	SAND	LOOSE	SILT	
5	X	3	2		GRAY	SAND	LOOSE		
	X	4	1		GRAY	SAND	V. LOOSE		-W/ HYDROCARBON OIL 6-12
	X	5	1		GRAY	SAND	V. LOOSE		
10		6	0.00		DARK GRAY + GRAY	CLAY	V. SOFT		
		7	0.00		REDISH BROWN + GRAY	CLAY	V. SOFT		-W/ROOTS
15		8	1.00		REDISH + YELLOW BROWN + GRAY	CLAY	STIFF		-W/ROOTS & Calc. Nods
		9	1.50		GRAY REDISH BROWN + GRAY	CLAY	STIFF		-W/ROOTS
		10	1.00		REDISH BROWN + GRAY	CLAY	STIFF		
20		11	0.25		DARK GRAY	CLAY	SOFT		DARK GRAY CLAY ~ 20 -W/ HYDROCARBON OIL 20-26
		12	0.25		DARK GRAY + GRAY	CLAY	SOFT		
25		13	0.25		DARK GRAY + GRAY	CLAY	SOFT		J = JAR SAMPLE
30									
35									