

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE NO.	PEN./TORVANE SPT.-BLOW COUNT	BORING NO. <u>51-63</u> DATE: BEGIN <u>10-10-02</u> PAGE <u>111</u> JOB NO. <u>1140127279</u> COMPLETE <u>10-10-02</u> Thin Walled Tube PROJECT <u>Lost Lake Placement Area</u> ☒ 3" ☐ 6" LOCATION <u>X=3,241,600.062, Y=723,942.730</u> ELEVATION OF HOLE _____ MANUFACTURER'S DESIGNATION OF DRILL RIG <u>CF-1000 Marsh Buggy</u> GROUNDWATER: DEPTH <u>B</u> ft., ELEV. _____ ft., at end of Drilling WEATHER <u>CLOUDY</u> DRILLER <u>Dempsey Gacaren</u> LOGGER <u>John A. Gentry</u>				
				COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS
0		1	0.75	BROWN + GRAY REDDISH BROWN	SAND	V. LOOSE		-w/ROOTS 0-7'
		2	0.75	BROWN + GRAY	CLAY	M. STIFF		-w/ SAND SMS + SHELL FRAC
		3	0.75	BROWN + GRAY	CLAY	M. STIFF		-w/ SAND SMS
-5		4	0.75	BROWN + GRAY	CLAY	M. STIFF		-w/ SAND SMS
		5	0.75	BROWN + GRAY	CLAY	M. STIFF		-w/ SAND SMS
		6	0.50	BROWN + GRAY	CLAY	M. STIFF		-w/ SAND SMS
-10		7	2.2	GRAY	SAND	V. LOOSE		
		8	0.00	DARK GRAY	CLAY	V. SOFT		* DARK GRAY CLAY @ 12'
-15		9	0.00	DARK GRAY	CLAY	V. SOFT		-w/ SAND SMS
		10	0.00	DARK GRAY	CLAY	V. SOFT		-w/ SAND SMS
								-w/ SAND ON BOTTOM 18'
-20								
-25								
-30								
-35								

J = JAR SAMPLE