

U.S. ARMY CORPS OF ENGINEERS

DEPTH, FEET		SAMPLE NO.	PEN./TORVANE	SPT.-BLOW COUNT	BORING NO. <u>E1-02</u>	DATE: BEGIN <u>10-18-02</u>	PAGE <u>1 11</u>
					JOB NO. <u>1140127279</u>	COMPLETE <u>10-18-02</u>	Thin Walled Tube
					PROJECT <u>Lost Lake Placement Area</u>	☒ 3"	☐ 6"
					LOCATION <u>X=3,243,766.376</u>	<u>Y=727,617.049</u>	
					ELEVATION OF HOLE		
					MANUFACTURER'S DESIGNATION OF DRILL RIG <u>CF-1000 Marsh Buggy</u>		
					GROUNDWATER: DEPTH	ft., ELEV.	ft., at end of Drilling
					WEATHER <u>PARTLY CLOUDY</u>		
					DRILLER <u>Dempsey Gearen</u>	LOGGER <u>John A. Gentry</u>	
		COLOR	MATERIAL TYPE	CONSISTENCY	SECONDARY CONSTITUENTS	STRUCTURAL FEATURES AND COMMENTS	
0	1	1/25	Brown GRAY CLAY	STIFF			
	2	1/50	REDDISH BROWN + GRAY CLAY	STIFF			
5	3	1/25	REDDISH BROWN + GRAY CLAY	STIFF			-W/ SAND SMS
	4	1/00	BROWN + GRAY CLAY	STIFF			-W/ SAND SMS
	5	1/50	REDDISH BROWN + GRAY CLAY	STIFF			-W/ SAND SMS
10	6	0/50	REDDISH BROWN + GRAY CLAY	STIFF			-W/ SAND SMS
	7	0/50	REDDISH BROWN + GRAY CLAY	STIFF			
15	8	0/25	REDDISH BROWN + GRAY CLAY	SOFT			
	9	0/25	GRAY CLAY	SOFT			-W/ SAND SMS + SHELL FRAG
	10		GRAY SAND	LOOSE	SILT		
20	11	1/23	GRAY + BROWN SILT	LOOSE			
	12	0/00	DARK GRAY + GRAY CLAY	USOFT			DARK GRAY CLAY @ 22' - W/ HYDROCARBON @ 22' - 28'
25	13	0/00	GRAY CLAY	USOFT			
	14	0/00	DARK GRAY + GRAY CLAY	USOFT			
30							
35							