## LOG OF BORING

		L-\
PROJECT:	White Point Island Restoration	

Nueces Bay - Corpus Christi, Texas

CLIENT:

Shiner Moseley & Associates, Inc. Corpus Christi, Texas

PROJECT NO. BORING NO.

1600-0159 B-11

DATE ELEV.

9/20/2000 NA

													SHEET 1 of 1		
	FIELD DATA LABORATORY DATA					DRY DA	ATA			DRILLING METHOD (S):					
SOIL SYMBOL			Ž	5	ATTERBERG							~	Wet Rotary		
	DЕРТН (FT)	SAMPLES	N. BLOWS/FT P: TONS/SQ FT T: TON/SQ FT PERCENT RECOVERY/	MOISTURE CONTENT	LIQUID LIMIT	PLASTIC LIMIT	PLASTICITY INDEX	DRY DENSITY POUNDS/CU.FT	SHEAR STRENGTH (KIPS/SQ FT)	FAILURE STRAIN (%)	CONFINING PRESSURE (POUNDS/SQ IN)	MINUS NO. 200 SIEVE (%)	GROUNDWATER INFORMATION:  Depth of water from surface to mudline at time of drilling was 3.0 ft.		
SOI	DEP	SAN	S	M	LL	PL	PI	Pou	STR STR	FAII	00 00	M	DESCRIPTION OF STRATUM		
			N=WH										No sample recovery, 0' to 4'.		
			N=WH												
	- 5	$\frac{1}{\sqrt{2}}$	N=WH	52									Clay, very soft, dark gray, with shell fragments and sand pockets. (CH)		
		$\bigvee$	N=WH	95	88	29	59								
			N=WH	65											
	- 10 -												TOTAL DEPTH = 10 FT (Below Mudline)		
	15 -	-													
		]													
													·		
			DARD PE							ANC	 E		REMARKS:		
P - POCKET PENETROMETER RESISTANCE T - POCKET TORVANE SHEAR STRENGTH											PLATE 12  FUGRO SOUTH INC Gulf Coast Testing				