



Aptim Environmental & Infrastructure, LLC
 6401 Congress Avenue, Suite 140
 Boca Raton, Florida 33487
 Phone # 1-561-391-8102

Legend for Geotechnical Data

Grain Size Scale for Sediments

Unified Soil Classification System (USCS) (ASTM D2487/2488)		APTIM Standard Sieve Stack		
		Sieve Number	Size (phi)	Size (mm)
Gravel	Coarse Gravel	3/4	-4.25	19.03
		5/8	-4.00	16.00
	Fine Gravel	7/16	-3.50	11.20
		5/16	-3.00	8.00
		3 1/2	-2.50	5.60
Sand	Coarse Sand	4	-2.25	4.75
		5	-2.00	4.00
		7	-1.50	2.80
	Medium Sand	10	-1.00	2.00
		14	-0.50	1.40
		18	0.00	1.00
		25	0.50	0.71
	Fine Sand	35	1.00	0.50
		45	1.50	0.36
		60	2.00	0.25
80		2.50	0.18	
120		3.00	0.13	
Fines	Silt/Clay	170	3.50	0.09
		200	3.75	0.08
		230	4.00	0.06

Proportional Definition of Descriptive Terms

<u>Descriptive Term</u>	<u>Range of Proportions</u>
Sandy, gravelly, etc.	35 % to 50 %
Some	20 % to 35 %
Little	10 % to 20 %
Trace	1 % to 10 %






















Consistency of Cohesive Soils

Description	Consistency Index	Approximate Undrained Shear Strength (kPa)	Field Identification
Hard		Over 300	Indented with difficulty by thumbnail, brittle.
Very Stiff	>1	150-300	Readily indented by thumbnail, still very tough.
Stiff	0.75-1	75-150	Readily indented by thumb but penetrated only with difficulty. Cannot be moulded in the fingers.
Firm	0.5-0.75	40-75	Can be penetrated several centimeters by thumb with moderate effort and moulded in fingers by strong pressure.
Soft	<0.5	20-40	Easily penetrated several centimeters by thumb, easily moulded.
Very Soft		Less than 20	Easily penetrated several centimeters by fist, exudes between fingers when squeezed in fist.


Source: Engineering Properties of Soils and Rocks, Fourth Edition by Fred G. Bell










USCS Classifications

Refers to the Army Corps of Engineers Unified Soils Classification System. Class types are defined primarily by grain size, sorting and percent of material passing the #200 sieve. Classification of materials on the core logs based on visual field examinations are identified on the core logs under the Classification of Materials Description. Classifications based on laboratory sieve analyses are identified on the core logs in the Legend and under Remarks.

GW		Well graded gravels or gravel-sand mixtures, little or no fines	ML		Inorganic silts and very fine sands, rock flour, sandy silts or clayey silts with slight plasticity
GP		Poorly graded gravels or gravel-sand mixtures, w/ little or no fines	MH		Inorganic silts, micaceous or diatomaceous fine sandy or silty soil, elastic silts
GM		Silty gravels, gravel-sand-silt mixtures	OL		Organic silts and organic silt-clays of low plasticity
GC		Clayey gravels, gravel-sand-clay mixtures	OH		Organic clays of medium to high plasticity, organic silts
SW		Well graded sands or gravelly sands, little or no fines	CL		Inorganic clays of low to medium plasticity, gravelly clays, sandy clays, silty clays, lean clays
SP		Poorly graded sands or gravelly sands, little or no fines	CH		Inorganic clays of high plasticity, fat clays
SM		Silty sands, sand-silt mixtures	PT		Peat and other highly organic soils
SC		Clayey sands, sand-clay mixtures	SP-SM		Poorly-graded silty sand
SW-SM		Well-graded silty sand	SM-SC		Silty clayey sand
GW-GM		Well-graded silty gravel	ML-CL		Inorganic silty lean clay
GM-GC		Clayey silty gravel			

Note: Information is after ACOE Atlantic Division Manual # 1110-1-1 titled *Engineering and Design Geotechnical Manual for Surface and Subsurface Investigations*

DRILLING LOG		DIVISION	INSTALLATION	SHEET 1
1. PROJECT TX GLO Region 1 Recon Geotechnical Sand Search Jefferson, Chambers, Galveston and Brazoria Co.				9. SIZE AND TYPE OF BIT 3.0 In.
2. BORING DESIGNATION TXGLO1-VC-23-007		LOCATION COORDINATES (ft) X = 3,557,233 Y = 13,801,297		10. COORDINATE SYSTEM/DATUM Texas State Plane South
3. DRILLING AGENCY APTIM		CONTRACTOR FILE NO.		HORIZONTAL NAD 1983 VERTICAL NAVD88
4. NAME OF DRILLER APTIM		11. MANUFACTURER'S DESIGNATION OF DRILL APTIM SEAS VC-700 Vibracore		<input type="checkbox"/> AUTO HAMMER <input type="checkbox"/> MANUAL HAMMER
5. DIRECTION OF BORING <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED		DEG. FROM VERTICAL	BEARING	12. TOTAL SAMPLES 0
6. THICKNESS OF OVERBURDEN 0.0 Ft.		13. TOTAL NUMBER CORE BOXES		DISTURBED 0 UNDISTURBED (UD) 2
7. DEPTH DRILLED INTO ROCK 0.0 Ft.		14. ELEVATION GROUND WATER		15. DATE BORING 10-06-23
8. TOTAL DEPTH OF BORING 19.3 Ft.		16. ELEVATION TOP OF BORING -24.5 Ft.		COMPLETED 10-06-23
		17. TOTAL RECOVERY FOR BORING 17.8 Ft.		18. SIGNATURE AND TITLE OF INSPECTOR SM

ELEV. (ft)	DEPTH (ft)	LEGEND	CLASSIFICATION OF MATERIALS Depths and elevations based on measured values	% REC.	BOX OR SAMPLE	REMARKS The USCS classification system defines silt as the percent passing the No.200 (0.075 mm) sieve
-24.5	0.0					
			LEAN CLAY, very soft, trace shell hash, trace silt, silt distributed in laminae, shell hash laminae @ 1.2' and 2.8', dark grayish brown (2.5Y-4/2), (CL).			
-29.0	4.5					
			Clayey SILT, trace sand, fine grained, quartz, trace shell hash, clay increases with depth in layer, 1.0" sandy pocket with shell hash @ 5.7', dark gray (2.5Y-4/1), (ML).			
-31.0	6.5					
			Sandy SILT, trace clay, trace shell hash, sand component is very fine grained quartz, clay interbedded throughout layer, color is mottled dark gray (2.5Y-4/1) and dark greenish gray (5GY-4/1), (ML).			
-33.1	8.6					
			FAT CLAY, hard, little sand, very fine grained, quartz, trace organics, trace silt, trace whole shell, sand increases with depth in layer, oxidation throughout layer, 1.5" organic pocket @ 8.8', 0.25" whole bivalve @ 9.8', light olive brown (2.5Y-5/3), (CH).		T1	Sample #T1, Depth = 9.0' Ave. Field Vane (tsf): 0.56
-34.4	9.9					
			Sandy LEAN CLAY, firm, trace silt, sand component is very fine grained quartz, sand decreases with depth in layer, 1.5" oxidized pocket @ 10.7', 0.5" oxidized pocket @ 11.6', brown (10YR-5/3), (CL).			
-38.0	13.5					
			FAT CLAY, stiff, little silt, trace sand, very fine grained, quartz, sand decreases with depth in layer, oxidation throughout layer, grayish brown (2.5Y-5/2), (CH).		T2	Sample #T2, Depth = 15.1' Ave. Field Vane (tsf): 0.15
-40.2	15.7					
			Clayey SAND, very fine grained, quartz, trace silt, clay interbedded throughout layer, clay decreases with depth in layer, color is mottled grayish brown (2.5Y-5/2) and olive brown (2.5Y-4/4), (SC).			
-41.0	16.5					
			SAND, fine grained, quartz, trace clay, trace silt, 0.5" clay pockets @ 16.7" and 17.1", dark yellowish brown (10YR-4/4), (SP).			
-41.8	17.3					
			FAT CLAY, stiff, trace sand, very fine grained, quartz, trace silt, 0.5" sand pocket @ 17.5', possible bioturbation @ 17.5', Bit sample from 17.6' to 17.8', olive brown (2.5Y-4/3), (CH).			
-42.3	17.8					
			No recovery.			
-43.8	19.3					
			End of Boring			

REGION 1 RECON GEOTECH.GP.1 3/25/24



Texas General
Land Office

Texas GLO
Region 1
Geotechnical
Reconnaissance
Survey

TXGLO1-VC-23-007

Date Collected: 10/6/23
Top Elev. (ft NAVD88): -24.5
Bottom Elev. (ft NAVD88): -42.3
Core Length (ft): 17.8



6401 Congress Avenue, Suite 140
Boca Raton, FL 33487
www.aptim.com
(561)391-8102



Mini Vane Shear Test Results

CORE ID	SAMPLE DEPTH (ft)	TORVANE (kg/cm ²)	TORVANE (tsf)	TORVANE (kpa)	DESCRIPTION ¹
TXGLO1-VC-23-001	No Torvane Conducted				
TXGLO1-VC-23-002	3.0	1.5	0.15	147.10	Stiff
	6.0	1.0	0.10	98.07	Stiff
TXGLO1-VC-23-003	10.3	4.5	0.46	441.30	Hard
	13.4	5.5	0.56	539.37	Hard
	16.3	2.5	0.26	245.17	Very Stiff
TXGLO1-VC-23-004	9.1	3.0	0.31	294.20	Very Stiff
	11.9	5.0	0.51	490.33	Hard
	14.1	6.0	0.61	588.40	Hard
TXGLO1-VC-23-005	4.8	6.0	0.61	588.40	Hard
	7.5	5.0	0.51	490.33	Hard
	13.5	5.5	0.56	539.37	Hard
	16.5	3.5	0.36	343.23	Hard
TXGLO1-VC-23-006	No Torvane Conducted				
TXGLO1-VC-23-007	9.0	5.5	0.56	539.37	Hard
	15.1	1.5	0.15	147.10	Stiff
TXGLO1-VC-23-008	7.1	5.5	0.56	539.37	Hard
	8.1	9.0	0.92	882.60	Hard
	10.2	8.0	0.82	784.53	Hard
	16.0	8.0	0.82	784.53	Hard
TXGLO1-VC-23-009	No Torvane Conducted				
TXGLO1-VC-23-010	8.0	7.0	0.72	686.47	Hard
	10.0	8.5	0.87	833.57	Hard
	12.5	9.5	0.97	931.63	Hard
TXGLO1-VC-23-011	4.4	5.5	0.56	539.37	Hard
	16.0	6.5	0.67	637.43	Hard
TXGLO1-VC-23-012	0.8	0.0	0.00	0.00	Very Soft
	2.6	1.0	0.10	98.07	Stiff
TXGLO1-VC-23-013	3.0	2.5	0.26	245.17	Very Stiff
	6.4	3.0	0.31	294.20	Very Stiff
	13.7	8.0	0.82	784.53	Hard
TXGLO1-VC-23-014	0.8	0.0	0.00	0.00	Very Soft
	1.9	2.0	0.20	196.13	Very Stiff
	5.0	2.5	0.26	245.17	Very Stiff
	10.0	2.8	0.28	269.68	Very Stiff
	18.0	3.0	0.31	294.20	Very Stiff
TXGLO1-VC-23-015	No Torvane Conducted				
TXGLO1-VC-23-016	2.4	7.0	0.72	686.47	Hard
	5.5	7.5	0.77	735.50	Hard