



Aptim Environmental & Infrastructure, LLC

6401 Congress Avenue, Suite 140

Boca Raton, Florida 33487

Phone # 1-561-391-8102

Legend for Geotechnical Data

Grain Size Scale for Sediments

Unified Soil Classification System (USCS) (ASTM D2487/2488)		APTIM Standard Sieve Stack		
		Sieve Number	Size (phi)	Size (mm)
Gravel	Coarse Gravel	3/4	-4.25	19.03
	Fine Gravel	5/8	-4.00	16.00
		7/16	-3.50	11.20
		5/16	-3.00	8.00
		3 1/2	-2.50	5.60
		4	-2.25	4.75
Sand	Coarse Sand	5	-2.00	4.00
		7	-1.50	2.80
		10	-1.00	2.00
	Medium Sand	14	-0.50	1.40
		18	0.00	1.00
		25	0.50	0.71
		35	1.00	0.50
	Fine Sand	45	1.50	0.36
		60	2.00	0.25
		80	2.50	0.18
		120	3.00	0.13
		170	3.50	0.09
		200	3.75	0.08
Fines	Silt/Clay	230	4.00	0.06

Proportional Definition of Descriptive Terms

<u>Descriptive Term</u>	<u>Range of Proportions</u>
Sandy, gravelly, etc.	35 % to 50 %
Some	20 % to 35 %
Little	10 % to 20 %
Trace	1 % to 10 %

Consistency of Cohesive Soils

Description	Consistency Index	Approximate Undrained Shear Strength (kPa)	Field Identification
Hard		Over 300	Indented with difficulty by thumbnail, brittle.
Very Stiff	>1	150-300	Readily indented by thumbnail, still very tough.
Stiff	0.75-1	75-150	Readily indented by thumb but penetrated only with difficulty. Cannot be moulded in the fingers.
Firm	0.5-0.75	40-75	Can be penetrated several centimeters by thumb with moderate effort and moulded in fingers by strong pressure.
Soft	<0.5	20-40	Easily penetrated several centimeters by thumb, easily moulded.
Very Soft		Less than 20	Easily penetrated several centimeters by fist, exudes between fingers when squeezed in fist.

Source: *Engineering Properties of Soils and Rocks, Fourth Edition by Fred G. Bell*

USCS Classifications

Refers to the Army Corps of Engineers Unified Soils Classification System. Class types are defined primarily by grain size, sorting and percent of material passing the #200 sieve. Classification of materials on the core logs based on visual field examinations are identified on the core logs under the Classification of Materials Description. Classifications based on laboratory sieve analyses are identified on the core logs in the Legend and under Remarks.


GW		Well graded gravels or gravel-sand mixtures, little or no fines	ML		Inorganic silts and very fine sands, rock flour, sandy silts or clayey silts with slight plasticity
GP		Poorly graded gravels or gravel-sand mixtures, w/ little or no fines	MH		Inorganic silts, micaceous or diatomaceous fine sandy or silty soil, elastic silts
GM		Silty gravels, gravel-sand-silt mixtures	OL		Organic silts and organic silt-clays of low plasticity
GC		Clayey gravels, gravel-sand-clay mixtures	OH		Organic clays of medium to high plasticity, organic silts
SW		Well graded sands or gravelly sands, little or no fines	CL		Inorganic clays of low to medium plasticity, gravelly clays, sandy clays, silty clays, lean clays
SP		Poorly graded sands or gravelly sands, little or no fines	CH		Inorganic clays of high plasticity, fat clays
SM		Silty sands, sand-silt mixtures	PT		Peat and other highly organic soils
SC		Clayey sands, sand-clay mixtures	SP-SM		Poorly-graded silty sand
SW-SM		Well-graded silty sand	SM-SC		Silty clayey sand
GW-GM		Well-graded silty gravel	ML-CL		Inorganic silty lean clay
GM-GC		Clayey silty gravel			

Note: Information is after ACOE Atlantic Division Manual # 1110-1-1 titled *Engineering and Design Geotechnical Manual for Surface and Subsurface Investigations*

DRILLING LOG		DIVISION	INSTALLATION	SHEET 1
1. PROJECT TX GLO Region 1 Recon Geotechnical Sand Search Jefferson, Chambers, Galveston and Brazoria Co.			9. SIZE AND TYPE OF BIT 3.0 In.	
2. BORING DESIGNATION TXGLO1-VC-23-037			10. COORDINATE SYSTEM/DATUM Texas State Plane South	HORIZONTAL NAD 1983
3. DRILLING AGENCY APTIM			11. MANUFACTURER'S DESIGNATION OF DRILL <input type="checkbox"/> AUTO HAMMER APTIM SEAS VC-700 Vibracore <input type="checkbox"/> MANUAL HAMMER	
4. NAME OF DRILLER APTIM			12. TOTAL SAMPLES DISTURBED UNDISTURBED (UD) 0 5	
5. DIRECTION OF BORING <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			13. TOTAL NUMBER CORE BOXES	
6. THICKNESS OF OVERBURDEN 0.0 Ft.			14. ELEVATION GROUND WATER	
7. DEPTH DRILLED INTO ROCK 0.0 Ft.			15. DATE BORING STARTED COMPLETED 10-09-23 10-09-23	
8. TOTAL DEPTH OF BORING 19.4 Ft.			16. ELEVATION TOP OF BORING -43.2 Ft.	
			17. TOTAL RECOVERY FOR BORING 19.1 Ft.	
			18. SIGNATURE AND TITLE OF INSPECTOR SM	

ELEV. (ft)	DEPTH (ft)	LEGEND	CLASSIFICATION OF MATERIALS Depths and elevations based on measured values	% REC.	BOX OR SAMPLE	REMARKS The USCS classification system defines silt as the percent passing the No.200 (0.075 mm) sieve
-43.2	0.0					
-45.4	2.2		Silty FAT CLAY, very stiff, oxidation between 0.3' & 0.7', greenish gray (10GY-5/1), (CH).		T1	Sample #T1, Depth = 1.0' Ave. Field Vane (tsf): 0.28
-49.7	6.5		FAT CLAY, hard, little silt, silt typically distributed throughout layer, silt decreases with depth in layer, silt pockets up to 0.25" between 4.4' & 4.6', greenish gray (5G-5/1), (CH).		T2	Sample #T2, Depth = 5.0' Ave. Field Vane (tsf): 0.41
-51.1	7.9		FAT CLAY, very stiff, trace sand, fine grained, quartz, trace silt, sand decreases with depth in layer, greenish gray (10Y-5/1), (CH).		T3	Sample #T3, Depth = 7.2' Ave. Field Vane (tsf): 0.26
-59.2	16.0		FAT CLAY, stiff to very stiff, little silt, trace sand, fine grained, quartz, trace wood fragments, silt distributed throughout layer and in laminae, 1.5" sand pocket @ 14.5', 1.0" pocket of wood fragments @ 15.3', dark gray (10YR-4/1), (CH).		T4	Sample #T4, Depth = 11.5' Ave. Field Vane (tsf): 0.15
-61.8	18.6		FAT CLAY, stiff, some organics, little silt, trace sand, fine grained, quartz, organics distributed in pockets up to 2.0", silt distributed in laminae, sand distributed in pockets up to 1.0", very dark gray (10YR-3/1), (CH).		T5	Sample #T5, Depth = 15.5' Ave. Field Vane (tsf): 0.26
-62.3	19.1		WOOD FRAGMENTS, little sand, fine grained, quartz, trace silt, wood fragments up to 1.5", black (10YR-2/1), (PT).			
-62.6	19.4		No recovery.			
			End of Boring			

REGION 1 RECON GEOTECH GP-1 3/25/24



Texas General
Land Office

Texas GLO
Region 1
Geotechnical
Reconnaissance
Survey

TXGLO1-VC-23-037

Date Collected: 10/9/23
Top Elev. (ft NAVD88): -43.2
Bottom Elev. (ft NAVD88): -62.3
Core Length (ft): 19.1



Mini Vane Shear Test Results

CORE ID	SAMPLE DEPTH (ft)	TORVANE (kg/cm ²)	TORVANE (tsf)	TORVANE (kpa)	DESCRIPTION ¹
TXGLO1-VC-23-029	2.7	1.3	0.13	122.58	Stiff
	5.3	2.0	0.20	196.13	Very Stiff
	11.4	1.5	0.15	147.10	Stiff
	14.0	1.5	0.15	147.10	Stiff
TXGLO1-VC-23-030	No Torvane Conducted				
TXGLO1-VC-23-031	0.5	4.8	0.49	465.82	Hard
	3.4	4.3	0.44	416.78	Hard
	7.1	6.0	0.61	588.40	Hard
	11.9	5.5	0.56	539.37	Hard
	15.8	3.5	0.36	343.23	Hard
TXGLO1-VC-23-032	2.5	3.0	0.31	294.20	Very Stiff
	6.0	5.0	0.51	490.33	Hard
	10.7	2.5	0.26	245.17	Very Stiff
	14.6	6.5	0.67	637.43	Hard
	16.0	5.5	0.56	539.37	Hard
	17.8	8.0	0.82	784.53	Hard
TXGLO1-VC-23-033	0.6	1.0	0.10	98.07	Stiff
	1.2	4.0	0.41	392.27	Hard
	4.1	6.0	0.61	588.40	Hard
	8.2	4.5	0.46	441.30	Hard
	11.7	4.0	0.41	392.27	Hard
TXGLO1-VC-23-034	2.0	4.5	0.46	441.30	Hard
	4.1	5.0	0.51	490.33	Hard
	7.1	4.0	0.41	392.27	Hard
	10.1	3.8	0.38	367.75	Hard
	13.4	4.2	0.43	411.88	Hard
	15.6	4.5	0.46	441.30	Hard
	18.2	4.0	0.41	392.27	Hard
TXGLO1-VC-23-035	2.2	3.0	0.31	294.20	Very Stiff
	5.0	4.0	0.41	392.27	Hard
	7.5	5.0	0.51	490.33	Hard
	18.0	5.5	0.56	539.37	Hard
TXGLO1-VC-23-036	3.0	1.0	0.10	98.07	Stiff
	8.0	0.8	0.08	73.55	Firm
	17.8	4.5	0.46	441.30	Hard
TXGLO1-VC-23-037	1.0	2.8	0.28	269.68	Very Stiff
	5.0	4.0	0.41	392.27	Hard
	7.2	2.5	0.26	245.17	Very Stiff
	11.5	1.5	0.15	147.10	Stiff
	15.5	2.5	0.26	245.17	Very Stiff