



## Aptim Environmental & Infrastructure, LLC

6401 Congress Avenue, Suite 140

Boca Raton, Florida 33487

Phone # 1-561-391-8102

### Legend for Geotechnical Data

#### Grain Size Scale for Sediments

Unified Soil Classification System (USCS) (ASTM D2487/2488)		APTIM Standard Sieve Stack		
		Sieve Number	Size (phi)	Size (mm)
Gravel	Coarse Gravel	3/4	-4.25	19.03
	Fine Gravel	5/8	-4.00	16.00
		7/16	-3.50	11.20
		5/16	-3.00	8.00
		3 1/2	-2.50	5.60
		4	-2.25	4.75
Sand	Coarse Sand	5	-2.00	4.00
		7	-1.50	2.80
		10	-1.00	2.00
	Medium Sand	14	-0.50	1.40
		18	0.00	1.00
		25	0.50	0.71
		35	1.00	0.50
	Fine Sand	45	1.50	0.36
		60	2.00	0.25
		80	2.50	0.18
		120	3.00	0.13
		170	3.50	0.09
		200	3.75	0.08
Fines	Silt/Clay	230	4.00	0.06

#### Proportional Definition of Descriptive Terms

<u>Descriptive Term</u>	<u>Range of Proportions</u>
Sandy, gravelly, etc.	35 % to 50 %
Some	20 % to 35 %
Little	10 % to 20 %
Trace	1 % to 10 %

#### Consistency of Cohesive Soils

Description	Consistency Index	Approximate Undrained Shear Strength (kPa)	Field Identification
Hard		Over 300	Indented with difficulty by thumbnail, brittle.
Very Stiff	>1	150-300	Readily indented by thumbnail, still very tough.
Stiff	0.75-1	75-150	Readily indented by thumb but penetrated only with difficulty. Cannot be moulded in the fingers.
Firm	0.5-0.75	40-75	Can be penetrated several centimeters by thumb with moderate effort and moulded in fingers by strong pressure.
Soft	<0.5	20-40	Easily penetrated several centimeters by thumb, easily moulded.
Very Soft		Less than 20	Easily penetrated several centimeters by fist, exudes between fingers when squeezed in fist.






Source: *Engineering Properties of Soils and Rocks, Fourth Edition by Fred G. Bell*


## USCS Classifications

Refers to the Army Corps of Engineers Unified Soils Classification System. Class types are defined primarily by grain size, sorting and percent of material passing the #200 sieve. Classification of materials on the core logs based on visual field examinations are identified on the core logs under the Classification of Materials Description. Classifications based on laboratory sieve analyses are identified on the core logs in the Legend and under Remarks.

GW		Well graded gravels or gravel-sand mixtures, little or no fines	ML		Inorganic silts and very fine sands, rock flour, sandy silts or clayey silts with slight plasticity
GP		Poorly graded gravels or gravel-sand mixtures, w/ little or no fines	MH		Inorganic silts, micaceous or diatomaceous fine sandy or silty soil, elastic silts
GM		Silty gravels, gravel-sand-silt mixtures	OL		Organic silts and organic silt-clays of low plasticity
GC		Clayey gravels, gravel-sand-clay mixtures	OH		Organic clays of medium to high plasticity, organic silts
SW		Well graded sands or gravelly sands, little or no fines	CL		Inorganic clays of low to medium plasticity, gravelly clays, sandy clays, silty clays, lean clays
SP		Poorly graded sands or gravelly sands, little or no fines	CH		Inorganic clays of high plasticity, fat clays
SM		Silty sands, sand-silt mixtures	PT		Peat and other highly organic soils
SC		Clayey sands, sand-clay mixtures	SP-SM		Poorly-graded silty sand
SW-SM		Well-graded silty sand	SM-SC		Silty clayey sand
GW-GM		Well-graded silty gravel	ML-CL		Inorganic silty lean clay
GM-GC		Clayey silty gravel			

Note: Information is after ACOE Atlantic Division Manual # 1110-1-1 titled *Engineering and Design Geotechnical Manual for Surface and Subsurface Investigations*

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1 SHEETS	
<b>1. PROJECT</b> TX GLO Region 1 Recon Geotechnical Sand Search Jefferson, Chambers, Galveston and Brazoria Co. 				<b>9. SIZE AND TYPE OF BIT</b> 3.0 In.			
<b>2. BORING DESIGNATION</b> TXGLO1-VC-23-039				<b>10. COORDINATE SYSTEM/DATUM</b> Texas State Plane South		<b>HORIZONTAL</b> NAD 1983	
<b>LOCATION COORDINATES (ft)</b> X = 3,452,247 Y = 13,732,301				<b>11. MANUFACTURER'S DESIGNATION OF DRILL</b> APTIM SEAS VC-700 Vibracore			
<b>3. DRILLING AGENCY</b> APTIM				<b>12. TOTAL SAMPLES</b> 0		<b>DISTURBED</b> 4	
<b>4. NAME OF DRILLER</b> APTIM				<b>13. TOTAL NUMBER CORE BOXES</b>			
<b>5. DIRECTION OF BORING</b> <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				<b>14. ELEVATION GROUND WATER</b>			
<b>DEG. FROM VERTICAL</b>				<b>15. DATE BORING</b> 10-09-23			
<b>BEARING</b>				<b>COMPLETED</b> 10-09-23			
<b>6. THICKNESS OF OVERBURDEN</b> 0.0 Ft.				<b>16. ELEVATION TOP OF BORING</b> -43.1 Ft.			
<b>7. DEPTH DRILLED INTO ROCK</b> 0.0 Ft.				<b>17. TOTAL RECOVERY FOR BORING</b> 18.2 Ft.			
<b>8. TOTAL DEPTH OF BORING</b> 19.0 Ft.				<b>18. SIGNATURE AND TITLE OF INSPECTOR</b> WMM			
ELEV. (ft)	DEPTH (ft)	LEGEND	CLASSIFICATION OF MATERIALS Depths and elevations based on measured values	% REC.	BOX OR SAMPLE	REMARKS The USCS classification system defines silt as the percent passing the No.200 (0.075 mm) sieve	
-43.1	0.0						
-46.5	3.4		LEAN CLAY, hard, trace organics, trace sand, fine grained, quartz, trace shell hash, trace silt, trace whole shell, sand distributed in pockets up to 1.0", silt distributed in laminae, 2.0" whole articulated bivalve @ 0.1', (1.75" x 2.0") whole articulated bivalve @ 2.9', dark greenish gray (10Y-4/1), (CL).		T1	Sample #T1, Depth = 1.7' Ave. Field Vane (tsf): 0.36	
-53.0	9.9		FAT CLAY, very stiff, little sand, fine grained, quartz, trace organics, trace shell hash, trace whole shell, sand typically distributed in pockets up to 2.0" and laminae, (0.5" x 0.75") whole bivalve @ 4.0', very dark greenish gray (10Y-3/1), (CH).		T2	Sample #T2, Depth = 5.0' Ave. Field Vane (tsf): 0.31	
-57.8	14.7		FAT CLAY, very stiff, little organics, little sand, fine grained, quartz, trace shell fragments, trace silt, organics distributed in laminae, sand distributed in pockets up to 3.0", (0.5" x 0.75") bivalve fragment @ 11.7', very dark greenish gray (10Y-3/1), (CH).		T3	Sample #T3, Depth = 12.2' Ave. Field Vane (tsf): 0.20	
-61.3	18.2		FAT CLAY, hard, little sand, fine grained, quartz, trace organics, trace rock fragments, trace shell fragments, sand distributed in pockets up to 3.0", rock fragments are fragments of partially lithified clay, 0.19" rock fragment @ 17.4', (0.5" x 0.75") bivalve fragment @ bottom of layer, greenish black (10Y-2.5/1), (CH).		T4	Sample #T4, Depth = 16.0' Ave. Field Vane (tsf): 0.46	
-62.1	19.0		No recovery.				
			End of Boring				



Texas General  
Land Office

Texas GLO  
Region 1  
Geotechnical  
Reconnaissance  
Survey

**TXGLO1-VC-23-039**

Date Collected: 10/09/23  
Top Elev. (ft NAVD88): -43.1  
Bottom Elev. (ft NAVD88): -61.4  
Core Length (ft): 18.2



## Mini Vane Shear Test Results

CORE ID	SAMPLE DEPTH (ft)	TORVANE (kg/cm <sup>2</sup> )	TORVANE (tsf)	TORVANE (kpa)	DESCRIPTION <sup>1</sup>
TXGLO1-VC-23-038	3.0	7.5	0.77	735.50	Hard
	9.3	6.0	0.61	588.40	Hard
	15.8	4.0	0.41	392.27	Hard
TXGLO1-VC-23-039	1.7	3.5	0.36	343.23	Hard
	5.0	3.0	0.31	294.20	Very Stiff
	12.2	2.0	0.20	196.13	Very Stiff
	16.0	4.5	0.46	441.30	Hard
TXGLO1-VC-23-040	No Torvane Conducted				
TXGLO1-VC-23-041	1.5	2.0	0.20	196.13	Very Stiff
	17.5	8.0	0.82	784.53	Hard
TXGLO1-VC-23-042	0.6	3.5	0.36	343.23	Hard
	1.7	3.5	0.36	343.23	Hard
	3.3	4.0	0.41	392.27	Hard
	5.5	3.5	0.36	343.23	Hard
	7.7	4.5	0.46	441.30	Hard
	10.3	5.0	0.51	490.33	Hard
	13.0	2.8	0.28	269.68	Very Stiff
	15.0	1.5	0.15	147.10	Stiff
	17.0	1.8	0.18	171.62	Very Stiff
TXGLO1-VC-23-043	No Torvane Conducted				
TXGLO1-VC-23-044	0.7	1.0	0.10	98.07	Stiff
	3.0	5.0	0.51	490.33	Hard
	5.6	8.5	0.87	833.57	Hard
	9.0	6.0	0.61	588.40	Hard
TXGLO1-VC-23-045	1.1	1.5	0.15	147.10	Stiff
	2.3	4.5	0.46	441.30	Hard
	5.4	5.5	0.56	539.37	Hard
	9.5	6.0	0.61	588.40	Hard
	12.4	3.0	0.31	294.20	Very Stiff
	15.0	5.5	0.56	539.37	Hard
TXGLO1-VC-23-046	3.6	5.0	0.51	490.33	Hard
	6.4	5.5	0.56	539.37	Hard
	8.1	6.0	0.61	588.40	Hard
	9.8	4.5	0.46	441.30	Hard
	12.1	5.0	0.51	490.33	Hard
	14.4	2.5	0.26	245.17	Very Stiff
	15.9	4.5	0.46	441.30	Hard
	17.4	3.5	0.36	343.23	Hard
	18.6	3.5	0.36	343.23	Hard
TXGLO1-VC-23-047	4.5	8.0	0.82	784.53	Hard
	9.8	10.0	1.02	980.67	Hard