



**Aptim Environmental & Infrastructure, LLC**  
 6401 Congress Avenue, Suite 140  
 Boca Raton, Florida 33487  
 Phone # 1-561-391-8102

## Legend for Geotechnical Data

### Grain Size Scale for Sediments

| Unified Soil Classification System (USCS) (ASTM D2487/2488) |               | APTIM Standard Sieve Stack |            |           |
|---|---------------|----------------------------|------------|-----------|
|   |               | Sieve Number               | Size (phi) | Size (mm) |
| Gravel  | Coarse Gravel | 3/4                        | -4.25      | 19.03     |
|   |               | 5/8                        | -4.00      | 16.00     |
|   | Fine Gravel   | 7/16                       | -3.50      | 11.20     |
|   |               | 5/16                       | -3.00      | 8.00      |
|   |               | 3 1/2                      | -2.50      | 5.60      |
| Sand  | Coarse Sand   | 4                          | -2.25      | 4.75      |
|   |               | 5                          | -2.00      | 4.00      |
|   |               | 7                          | -1.50      | 2.80      |
|   | Medium Sand   | 10                         | -1.00      | 2.00      |
|   |               | 14                         | -0.50      | 1.40      |
|   |               | 18                         | 0.00       | 1.00      |
|   |               | 25                         | 0.50       | 0.71      |
|   | Fine Sand     | 35                         | 1.00       | 0.50      |
|   |               | 45                         | 1.50       | 0.36      |
|   |               | 60                         | 2.00       | 0.25      |
| 80  |               | 2.50                       | 0.18       |           |
| 120   |               | 3.00                       | 0.13       |           |
| Fines   | Silt/Clay     | 170                        | 3.50       | 0.09      |
|   |               | 200                        | 3.75       | 0.08      |
|   |               | 230                        | 4.00       | 0.06      |

### Proportional Definition of Descriptive Terms

| <u>Descriptive Term</u> | <u>Range of Proportions</u> |
|-------------------------|-----------------------------|
| Sandy, gravelly, etc.   | 35 % to 50 %                |
| Some                    | 20 % to 35 %                |
| Little                  | 10 % to 20 %                |
| Trace                   | 1 % to 10 %                 |






















### Consistency of Cohesive Soils

| Description | Consistency Index | Approximate Undrained Shear Strength (kPa) | Field Identification   |
|-------------|-------------------|--|--|
| Hard        |                   | Over 300                                   | Indented with difficulty by thumbnail, brittle.  |
| Very Stiff  | >1                | 150-300                                    | Readily indented by thumbnail, still very tough.   |
| Stiff       | 0.75-1            | 75-150                                     | Readily indented by thumb but penetrated only with difficulty. Cannot be moulded in the fingers.               |
| Firm        | 0.5-0.75          | 40-75                                      | Can be penetrated several centimeters by thumb with moderate effort and moulded in fingers by strong pressure. |
| Soft        | <0.5              | 20-40                                      | Easily penetrated several centimeters by thumb, easily moulded.  |
| Very Soft   |                   | Less than 20                               | Easily penetrated several centimeters by fist, exudes between fingers when squeezed in fist.                   |


*Source: Engineering Properties of Soils and Rocks, Fourth Edition by Fred G. Bell*

## USCS Classifications

Refers to the Army Corps of Engineers Unified Soils Classification System. Class types are defined primarily by grain size, sorting and percent of material passing the #200 sieve. Classification of materials on the core logs based on visual field examinations are identified on the core logs under the Classification of Materials Description. Classifications based on laboratory sieve analyses are identified on the core logs in the Legend and under Remarks.

|       |   |  |       |   |   |
|-------|---|--|-------|---|---|
| GW    |    | Well graded gravels or gravel-sand mixtures, little or no fines      | ML    |    | Inorganic silts and very fine sands, rock flour, sandy silts or clayey silts with slight plasticity |
| GP    |    | Poorly graded gravels or gravel-sand mixtures, w/ little or no fines | MH    |    | Inorganic silts, micaceous or diatomaceous fine sandy or silty soil, elastic silts                  |
| GM    |    | Silty gravels, gravel-sand-silt mixtures                             | OL    |    | Organic silts and organic silt-clays of low plasticity  |
| GC    |    | Clayey gravels, gravel-sand-clay mixtures                            | OH    |    | Organic clays of medium to high plasticity, organic silts   |
| SW    |   | Well graded sands or gravelly sands, little or no fines              | CL    |   | Inorganic clays of low to medium plasticity, gravelly clays, sandy clays, silty clays, lean clays   |
| SP    |  | Poorly graded sands or gravelly sands, little or no fines            | CH    |  | Inorganic clays of high plasticity, fat clays   |
| SM    |  | Silty sands, sand-silt mixtures                                      | PT    |  | Peat and other highly organic soils   |
| SC    |  | Clayey sands, sand-clay mixtures                                     | SP-SM |  | Poorly-graded silty sand  |
| SW-SM |  | Well-graded silty sand   | SM-SC |  | Silty clayey sand   |
| GW-GM |  | Well-graded silty gravel   | ML-CL |  | Inorganic silty lean clay   |
| GM-GC |  | Clayey silty gravel  |       |   |   |

Note: Information is after ACOE Atlantic Division Manual # 1110-1-1 titled *Engineering and Design Geotechnical Manual for Surface and Subsurface Investigations*

|  |  |   |  |  |
|--|--|---|--|--|
| <b>DRILLING LOG</b>  |  | <b>DIVISION</b>   | <b>INSTALLATION</b>                    | <b>SHEET 1</b>   |
| <b>1. PROJECT</b><br>TX GLO Region 1 Recon Geotechnical Sand Search<br>Jefferson, Chambers, Galveston and Brazoria Co.           |  |  | <b>9. SIZE AND TYPE OF BIT</b> 3.0 In. | <b>OF 1 SHEETS</b>   |
| <b>2. BORING DESIGNATION</b><br>TXGLO1-VC-23-049   |  | <b>10. COORDINATE SYSTEM/DATUM</b><br>Texas State Plane South                     |  | <b>HORIZONTAL</b><br>NAD 1983  |
| <b>3. DRILLING AGENCY</b><br>APTIM   |  | <b>11. MANUFACTURER'S DESIGNATION OF DRILL</b><br>APTIM SEAS VC-700 Vibracore     |  | <input type="checkbox"/> <b>AUTO HAMMER</b><br><input type="checkbox"/> <b>MANUAL HAMMER</b> |
| <b>4. NAME OF DRILLER</b><br>APTIM   |  | <b>12. TOTAL SAMPLES</b>  |  | <b>DISTURBED</b><br>0  |
| <b>5. DIRECTION OF BORING</b><br><input checked="" type="checkbox"/> <b>VERTICAL</b><br><input type="checkbox"/> <b>INCLINED</b> |  | <b>DEG. FROM VERTICAL</b>   | <b>BEARING</b>                         | <b>UNDISTURBED (UD)</b><br>5   |
| <b>6. THICKNESS OF OVERBURDEN</b> 0.0 Ft.  |  | <b>13. TOTAL NUMBER CORE BOXES</b>  |  | <b>14. ELEVATION GROUND WATER</b>  |
| <b>7. DEPTH DRILLED INTO ROCK</b> 0.0 Ft.  |  | <b>15. DATE BORING</b>  |  | <b>STARTED</b><br>10-10-23   |
| <b>8. TOTAL DEPTH OF BORING</b> 17.3 Ft.   |  | <b>16. ELEVATION TOP OF BORING</b> -35.2 Ft.                                      |  | <b>COMPLETED</b><br>10-10-23   |
|  |  | <b>17. TOTAL RECOVERY FOR BORING</b> 17.3 Ft.                                     |  | <b>18. SIGNATURE AND TITLE OF INSPECTOR</b><br>WMM   |

| ELEV. (ft) | DEPTH (ft) | LEGEND | CLASSIFICATION OF MATERIALS<br>Depths and elevations based on measured values  | % REC. | BOX OR SAMPLE | REMARKS<br>The USCS classification system defines silt as the percent passing the No.200 (0.075 mm) sieve |
|------------|------------|--------|--|--------|---------------|---|
| -35.2      | 0.0        |        |  |        |               |   |
| -37.7      | 2.5        |        | LEAN CLAY, soft, trace sand, fine grained, quartz, trace whole shell, sand laminae at bottom of layer, (1.0" x 2.0") partially lithified clay pocket @ 0.2', (0.5" x 0.75") whole bivalve shell @ 0.6', (1.0" x 2.0") sand pocket @ 1.3', dark gray (2.5Y-4/1), (CL).  |        |               |   |
| -38.4      | 3.2        |        | FAT CLAY, stiff, trace sand, fine grained, quartz, trace shell hash, sand distributed in laminae, shell hash decreases with depth in layer, gray (2.5Y-5/1), (CH).   |        | T1            | Sample #T1, Depth = 3.0' Ave. Field Vane (tsf): 0.15  |
| -39.7      | 4.5        |        | FAT CLAY, hard, trace shell hash, gray (2.5Y-6/1), (CH).   |        | T2            | Sample #T2, Depth = 4.0' Ave. Field Vane (tsf): 0.51  |
| -40.8      | 5.6        |        | FAT CLAY, stiff, trace rock fragments, trace shell hash, rock fragments are fragments of partially lithified clay throughout layer, light yellowish brown (2.5Y-6/3), (CH).  |        | T3            | Sample #T3, Depth = 5.1' Ave. Field Vane (tsf): 0.15  |
| -42.1      | 6.9        |        | FAT CLAY, stiff, some sand, fine grained, quartz, sand increases with depth in layer, 4.0" sand pocket @ 6.5', greenish gray (10Y-6/1), (CH).  |        |               |   |
|            |            |        | FAT CLAY, hard, trace organics, trace sand, fine grained, quartz, trace shell fragments, trace whole shell, sand distributed in pockets up to 2.0", organic lamina @ 8.4', whole bivalves up to 2.5" @ 9.9' and between 12.0' & 13.3', (1.5" x 2.0") whole articulated bivalve @ 10.1', shell fragments up to 2.0" between 12.0' & 13.3', color is mottled greenish gray (5GY-6/1) and light yellowish brown (10YR-6/4), (CH). |        | T4            | Sample #T4, Depth = 9.4' Ave. Field Vane (tsf): 0.67  |
| -49.0      | 13.8       |        | FAT CLAY, hard, trace organics, trace sand, fine grained, quartz, lenticular bedding throughout layer, possible bioturbation throughout layer, organic lamina @ 14.5', oxidation between 16.3' & 17.3', color is mottled white (5Y-8/1), dark yellowish brown (10YR-4/6) and olive gray (5Y-5/2), (CH).  |        | T5            | Sample #T5, Depth = 15.5' Ave. Field Vane (tsf): 0.97   |
| -52.5      | 17.3       |        | End of Boring  |        |               |   |

REGION 1 RECON GEOTECH.GPJ 3/25/24



Texas General  
Land Office

Texas GLO  
Region 1  
Geotechnical  
Reconnaissance  
Survey

**TXGLO1-VC-23-049**

Date Collected: 10/10/23  
Top Elev. (ft NAVD88): -35.2  
Bottom Elev. (ft NAVD88): -52.5  
Core Length (ft): 17.3

  
6401 Congress Avenue, Suite 140  
Boca Raton, FL 33487  
www.aptim.com  
(561)391-8102



## Mini Vane Shear Test Results

| CORE ID          | SAMPLE DEPTH (ft)    | TORVANE (kg/cm <sup>2</sup> ) | TORVANE (tsf) | TORVANE (kpa) | DESCRIPTION <sup>1</sup> |
|------------------|----------------------|-------------------------------|---------------|---------------|--------------------------|
| TXGLO1-VC-23-048 | 2.2                  | 2.8                           | 0.28          | 269.68        | Very Stiff               |
|                  | 4.8                  | 1.5                           | 0.15          | 147.10        | Stiff                    |
| TXGLO1-VC-23-049 | 3.0                  | 1.5                           | 0.15          | 147.10        | Stiff                    |
|                  | 4.0                  | 5.0                           | 0.51          | 490.33        | Hard                     |
|                  | 5.1                  | 1.5                           | 0.15          | 147.10        | Stiff                    |
|                  | 9.4                  | 6.5                           | 0.67          | 637.43        | Hard                     |
|                  | 15.5                 | 9.5                           | 0.97          | 931.63        | Hard                     |
| TXGLO1-VC-23-050 | 4.8                  | 1.0                           | 0.10          | 98.07         | Stiff                    |
|                  | 8.1                  | 1.5                           | 0.15          | 147.10        | Stiff                    |
|                  | 10.4                 | 2.0                           | 0.20          | 196.13        | Very Stiff               |
|                  | 11.7                 | 2.0                           | 0.20          | 196.13        | Very Stiff               |
|                  | 14.7                 | 2.5                           | 0.26          | 245.17        | Very Stiff               |
| TXGLO1-VC-23-051 | 1.0                  | 1.0                           | 0.10          | 98.07         | Stiff                    |
|                  | 1.8                  | 1.5                           | 0.15          | 147.10        | Stiff                    |
|                  | 3.1                  | 3.5                           | 0.36          | 343.23        | Hard                     |
|                  | 6.4                  | 10.0                          | 1.02          | 980.67        | Hard                     |
|                  | 11.0                 | 10.0                          | 1.02          | 980.67        | Hard                     |
| TXGLO1-VC-23-052 | 1.0                  | 0.0                           | 0.00          | 0.00          | Very Soft                |
|                  | 3.0                  | 0.0                           | 0.00          | 0.00          | Very Soft                |
|                  | 11.5                 | 7.5                           | 0.77          | 735.50        | Hard                     |
|                  | 14.6                 | 8.0                           | 0.82          | 784.53        | Hard                     |
|                  | 16.0                 | 9.0                           | 0.92          | 882.60        | Hard                     |
| TXGLO1-VC-23-053 | 0.5                  | 0.0                           | 0.00          | 0.00          | Very Soft                |
|                  | 2.2                  | 0.5                           | 0.05          | 49.03         | Firm                     |
|                  | 18.0                 | 2.5                           | 0.26          | 245.17        | Very Stiff               |
| TXGLO1-VC-23-054 | 0.6                  | 0.0                           | 0.00          | 0.00          | Very Soft                |
|                  | 2.2                  | 0.0                           | 0.00          | 0.00          | Very Soft                |
|                  | 7.0                  | 0.3                           | 0.03          | 24.52         | Soft                     |
|                  | 13.7                 | 1.0                           | 0.10          | 98.07         | Stiff                    |
| TXGLO1-VC-23-055 | 0.3                  | 0.5                           | 0.05          | 49.03         | Firm                     |
|                  | 1.6                  | 1.0                           | 0.10          | 98.07         | Stiff                    |
|                  | 3.1                  | 1.0                           | 0.10          | 98.07         | Stiff                    |
|                  | 8.9                  | 4.0                           | 0.41          | 392.27        | Hard                     |
|                  | 14.1                 | 4.8                           | 0.49          | 465.82        | Hard                     |
| TXGLO1-VC-23-056 | No Torvane Conducted |                               |               |               |                          |
| TXGLO1-VC-23-057 | 6.4                  | 1.5                           | 0.15          | 147.10        | Stiff                    |
| TXGLO1-VC-23-058 | 0.8                  | 0.5                           | 0.05          | 49.03         | Firm                     |
|                  | 4.2                  | 1.0                           | 0.10          | 98.07         | Stiff                    |
|                  | 12.9                 | 1.5                           | 0.15          | 147.10        | Stiff                    |
|                  | 15.5                 | 2.0                           | 0.20          | 196.13        | Very Stiff               |