

LOG OF BORING

Project : MTBE Improvement Areas-Tenneco Natural Gas Liquids Corp., La Porte, Texas
 Client : M.W. Kellogg Company
 Houston, Texas
 Boring No. : B-108
 File No. : 90-0422
 Date : 7-11-90
 Elevation : +18 ft.
 Dry Augered 0 to 12 ft. Water at 10.0 ft.; Caving at ft.
 Wash Bored 12 to 30 ft. Water at 5.1 ft. after 5 hours

ELEV	SOIL SYMBOLS SAMPLER SYMBOLS AND FIELD TEST DATA	Description	Wc (%)	Dens. (pcf)	Qu or UU (tsf)	Str (%)	LL	PI	#200 (%)
DEPTH									
0	4.50	Very stiff dark gray CLAY "FILL" w/calcareous nodules -w/roots & shell to 2'	15						
	4.25		20						
	1.75	-stiff below 4'	26						
5	1.75	-gray & tan below 6'	23	103	1.78	8			
	0.50	-w/silty sand layers @ 8'	24						
10	2.25	Stiff tan & gray CLAY (CH) w/slickensides	32						
	2.50								
15									
	3.00	-very stiff w/ferrous nodules below 18'							
20									
	3.25								
25									
	2.75	-stiff @ 28'							
30									

Bottom @ 30'