

Job No. 0401-2906 Completion Date 5/17/90 Time _____ Field Log of Boring 90-70

Elevation _____ Location Disposal Area No. 5 Driller R. AGUILAR

Lab. Tests	Soil Sample			Depth (ft)	Sample	Blows	Penet.	Logger <u>W. CUTSHALL</u>	
	No.	Depth	Type					Comments	Description of Material
									Fill: Intermixed loose sand and soft clay, brown
	1	3.5-5	J		X	1-3-2	-		
				5					
	2	5-7	Q				0.50		
	3	7-9	J				-		
	4	9-10.5	J	10	X	2-3-2	-		(14.0')
				15	X	1-1-1	-		
	5	14-15.5	J						
	6	19-20.5	J	20	X	1-1-2	-		- sandy clay layer below 20.5' (21.0')
	7	21-23	Q				2.25		
	8	23-25	Q				1.5	Bad Sample	
	9	25-27	Q	25			1.95	Bad Sample	
	10	27-29	J						(27.0')
				30					
	11	32.5-34	J		X	6-14-18	-		- with sandstone parting at 33.5'
				35					
	12	37.5-39	J		X	14-22-26	-		(40.0')
				40					

Remarks: 1) STAKE ON PEAK OF MOUND
OFFSET - 100' EAST NEAREST LEVEE &
± 5' LOWER ELEVATION


2) CASING SET TO 5' DEPTH.

Depth to Water 10.7' Caved at _____ Date _____ Time _____ ;

Boring Sealed? w/cuttings
Dry Auger _____ to _____ ft
Wet Rotary 0 to 40 ft
Water First Noticed _____ ft

SUMMARY OF TEST RESULTS
Galveston District, Corps of Engineers
Delivery Order No. 0016
Brazos Island Harbor
Brownsville Ship Channel

Boring Number	Sample Number	Sample Depth (ft)	Visual Classification	USCS	MC (%)	UDW (pcf)	LL	PL	PI	Gradation, % Passing Sieve No. 4 10 40 200				UNC Su (ksf)	TV Su (ksf)
90-70	1J	3.5-5	Gray and tan SANDY CLAY w/ cl sms & calc nods	CL	30										
90-70	2Q	5-7	Firm SANDY CLAY w/ calc deps and sa pkcts & sms	CL	27										
90-70	3J	7-9	Stiff brown CLAY w/ sand pockets	CH	18										
90-70	4J	9-10.5	Red CLAY with free water and sand	CH	65										
90-70	5J	14-15.5	Brown CLAY with shell fragments	CH	42		52				100	97	83		
90-70	6J	19-20.5	Brown CLAY with silt pockets	CH	35										
90-70	7Q	21-23	Stiff brown CLAY w/ ferrous stains	CH	36	86	60					100	99	1.4	
90-70	8Q	23-25	Firm brown CLAY with ferrous stain	CH	39										
90-70	9Q	25-27	Stiff brown CLAY	CH	38										
90-70	10J	27-29	Gray CLAYEY SAND w/ cl partings & seams	SC	23						100	78	34		
90-70	11J	32.5-34	Tan and greenish gray SANDY CLAY w/sa pockets	CL											
90-70	12J	37.5-39	Greenish gray SANDY CLAY w/ calc deposits	CL											
90-71	1Q	3-5	Stiff brown CLAY w/ fe stain & shell frag	CH	37		69								
90-71	2J	7.5-9	Brown fine SILTY SAND w/ clay pockets	SM											
90-71	3J	12.5-14	Brown fine SANDY SILT w/ clay pockets <i>v/loose</i>	ML	24						100	96	53		
90-71	4J	17.5-19	Brown fine SAND <i>Med Den</i>	SP ✓									47		
90-71	5J	20.5-24	Brown fine SAND w/ clay pockets <i>Dense</i>	SP ✓	23						100	47	15		
90-71	6J	27.5-29	Gray SANDY CLAY w/ sa seams & calc deposits <i>v/D</i>	CL SP											



STRESS-STRAIN CURVES
UNCONFINED COMPRESSION TEST